Material Safety Data Sheet # 100

For Printing Inks and related Materials OSHA Hazard Communication Standard, 29 CFR 1910.1200

 Updated:
 8/20/2012

 Supersedes:
 1/09/2012

 Origination Date:
 5/14/93

 MSDS#:
 100

I. PRODUCT IDENTIFICATION

Manufacturer: Gans Ink and Supply Co, Inc.		HMIS HAZARD IDENTIFICATION		
	441 Boyd Street Los Angeles, CA 90033			
	one: (323) 264-2200		Health Flammability	1
Lineigency pho	nic. (323) 20 1 -2200		Reactivity	0
			Personal Protection	В
Product Class: Lithographic Printing Ink		Manufacturer's code: Various, including A137785,		
		10699, A139350 to A139353, A140092, 80731,		
		A129566, A129568, A141815, A138068, A138073,		
		A138075, A138078, A138176, A138429, A138429,		
		A138433, A138434, A138459, A139226, A139355,		
		I011938,		

Trade Name: Ameriset, Camray Plus, Euro-Set, Falcon, Meteor, Nu-Era Heat Transfer, Optimum, Panda, Q/S, Roto-Web, Rubber Base Pantone (RBP) including warm and cool gray (RBW, RBC), Rubber Base Black, Seaside, Sunrise, Hi- VOC, SFP Pantone blending bases and spot colors, Offset Security Inks, 10699, G.C.M. Hi-Tac Proc. Series, Old Fashion Rotary, Bengal, Hexachrome, Creo Process, et al.

II. HAZARDOUS INGREDIENTS

II. HAZARDOUS INGREDIEN IS				
Material	CAS#	%	Exposure Limits	Units
Technical White Oils	8042-47-5	15-20	OSHA PEL 5 mg/m3	
			ACGIH TLV 5 mg/m3	
			ACGIH/ STEL 10 mg/m ³	}
Linseed Oil	67746-08-1	6.0	OSHA PEL No Lir ACGIH TLV No Lir ACGIH/ STEL No Lir	nit
Aliphatic Hydrocarbon Solvent proprietary exempt OSHA PEL oil mist is 5mg/m3				/m3
This product has not been identified as a carcinogen by OSHA Hazard Communication Standard (29 CFR 1910.1200)				

III. HEALTH HAZARD INFORMATION

Effects of Overexposure

Inhalation: This product has a low vapor pressure and is not expected to present an inhalation hazard at ambient conditions. Caution should be taken to prevent aerosolization or misting of this product. The threshold limit value (TLV) for this product as oil mist is 5 mg/M³. Exposures below 5 mg/M³ appear to be without significant health risk. Acute overexposure may result in irritation of the throat and lungs. Chronic exposure to high concentrations of aerosols or mists to laboratory animals has resulted in non-specific symptoms related to the nervous system, gastrointestinal tract, and lungs.

Skin Contact: Avoid skin contact. This product is non-irritating to the skin upon direct contact. Prolonged or repeated contact may result in contact dermatitis which is characterized by dryness, chapping, and

reddening. This condition may make the skin more susceptible to other irritants, sensitizers, and disease. Pre-existing skin conditions may make the skin more susceptible and facilitate uptake by this route.

Eye Contact: Avoid eye contact. This product may be slightly irritating to the eyes upon direct contact. This product has a low vapor pressure and is not expected to present a hazard to the eyes at ambient conditions. Exposure to high concentrations of vapors may be irritating to the eyes.

Ingestion: Do not ingest. Ingestion of small quantities is usually nonfatal unless aspiration occurs. Severe oral intoxication will lead to intense burning of the throat and may result in drowsiness, dullness, numbness, and headache followed by dizziness, weakness, and nausea. Loss of consciousness and convulsions followed by death may result. See *Notes to Physician* section below.

IV. FIRST AID PROCEDURES

Emergency & First Aid Procedures

Eyes: Immediately flush eyes with large amounts of water and continue flushing for 15 minutes until irritation subsides. If irritation persists, seek medical attention.

Skin: Remove contaminated clothing. Wash contaminated area thoroughly with soap and water. If redness or irritation occurs, seek medical attention.

Inhalation: This material has a low vapor pressure and is not expected to present an inhalation exposure at ambient conditions. If mist or exposure is generated when the material is heated or handled, remove victim from exposure. If breathing has stopped or is irregular, administer artificial respiration and supply oxygen if it is available. If victim is unconscious, remove to fresh air and seek medical attention.

Ingestion: Do not induce vomiting. Seek immediate medical attention.

Notes to Physician: Aspiration may lead to chemical pneumonitis which is characterized by pulmonary edema and hemorrhage, and may be fatal. Signs of lung involvement include increased respiration rate, increased heart rate, and a bluish discoloration of the skin. Coughing, choking, and gagging are often noted at the time if aspiration. Gastrointestinal discomfort may develop, followed by vomiting, with risk of aspiration.

V. FIRE AND EXPLOSION DATA

Flash Point °F: 260 °F (PMCC)	Auto-ignition	Temperature ° F: 428 ASTM E-659
Flammable Limits in Air (%	Lower Limit: No Data	Upper Limit: No Data
Volume)		

Extinguishing Media: Use water fog, foam, CO₂, or dry chemical extinguishing media.

Special Fire Fighting Procedures: Water may be ineffective, but can be used to cool containers exposed to heat or flame. Firefighters wear self contained breathing apparatus.

Unusual Fire & Explosion Hazard: Dense smoke may be generated while burning; carbon dioxide, carbon monoxide, and other oxides may be generated as products of combustion.

VI. ACCIDENTAL RELEASE

Steps to be taken in event of spill or release: Absorb with an inert material such as vermiculite, sand, dirt etc. Scrape up with trowel or scoop and place in a suitable container. Clean up with a suitable solvent. Do not allow to enter waterways.

VII. HANDLING AND STORAGE

Handling and Storage: Store in containers in a cool, well-ventilated area. Keep away from all sources of ignition, open flame or heat. Avoid prolonged contact with skin, contact with eyes, and breathing of mist or vapor. Always wash hands and face with soap and water before eating, drinking, and smoking

Other Precautions: For industrial use only. Do not ingest. Consumption of food and beverages should be avoided in work areas where hydrocarbons are present

VIII. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Ventilation Requirements: If vapor or mist is generated when the material is heated or handled, adequate ventilation in accordance with good engineering practice must be provided to maintain concentrations below the specific exposure or flammable limits.

Personal Protective Equipment

Respirator: Respiratory protection is not required under conditions of normal use. If vapor or mist is generated when the material is heated or handled, use an organic vapor respirator with a dust and mist filter. All respirators must be NIOSH certified. Do not use compressed oxygen in hydrocarbon atmospheres.

Skin: No skin protection is required for single, short duration exposures. For prolonged exposures, use impervious synthetic rubber clothing (boots, gloves, etc.) over parts of the body subject to exposure

Eye: Eye protection is not required under conditions of normal use. If material is handled such that it could be splashed into eyes, wear plastic face or splash-proof safety glasses or goggles.

IX. PHYSICAL AND CHEMICAL DATA

Boiling Range ° F: 517-588 °F	Vapor Density (Air = 1): 6.7	
Relative Density ($H_2O = 1$): 1.00-1.19	Vapor Pressure (mm Hg @ 68°F): 0.1	
Material Density Lbs./Gal: 8.40-9.95	Solubility in Water: Insoluble	
% Volatile Organic Compounds (VOC) by	% Solids by Weight: 80-85	
Weight: 15-20		
VOC: lbs/gal: 1.99 max g/L: 238 max	Appearance/Odor: Colored paste	

X. STABILITY AND REACTIVITY INFORMATION

	0 ; ; - 0 : ;			
Stability (Thermal, Light, etc.): Stable	Conditions to avoid: Excessive heat, open flame,			
	sources of ignition.			
Hazardous Polymerization: Will not occur.	Materials to avoid: Contact with strong oxidizers.			
Hazardous Decomposition Products: CO ₂ , CO, and other oxides may be generated as products of				
combustion.				

XI. TOXICOLOGICAL INFORMATION

CARCINOGEN: This product has not been identified as a carcinogen by OSHA or the National

Toxicology Program (NTP), or the International Agency for Research Cancer (IARC).

Mutagen:No DataTeratogen:No DataReproductive Toxicity:No Data

Acute Data:

White Mineral Oil - 8042-47- 5

Dermal LD50= 2g/kg

LC50= No information available

Oral LD50= 5g/kg (Rat)

Distillates, sweetened middle – 64741-86-2

LD50 Oral > 5,000 mg/kg (Rat)

LD50 Dermal > 2,000 mg/kg (Rabbit)

XII. ECOLOGICAL INFORMATION

This product has not been evaluated at this time. As with all products and chemicals, do not allow to enter waterways, sewers or drains.

XIII. DISPOSAL INFORMATION

Waste Disposal Method: If recycling as ink is not possible, material may be incinerated or land filled at a licensed facility in accordance with local, state, and federal regulations.

XIV. TRANSPORT INFORMATION

Flammability Classification:

OSHA: Class III B
DOT: Not Regulated
IMDG: Not Regulated

XV. REGULATORY INFORMATION

SARA Title III Section 313:

This material does Not contain chemicals subject to the reporting requirements of the SARA Superfund Amendments and Reauthorization Act.

TSCA Section 8(b) Inventory Status:

All component(s) of this product are either exempt or listed on the TSCA Inventory.

U.S. State Regulations

California Proposition 65:

This product does not intentionally contain any chemicals known by the state of California to cause cancer and/or reproductive harm. Moreover, Gans Ink and Supply Co., Inc. does not routinely analyze its products for impurities which may be such chemicals.

XVI. OTHER INFORMATION

The information herein is presented in good faith, based on the data available to us and is believed to be correct as of the date hereof. However, Gans Ink and Supply Co., Inc. makes no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Gans Ink and Supply Co., Inc. assumes no responsibility for any damages of any nature directly or indirectly resulting from the use of or reliance upon the information contained herein. Users must make their own determination as to the suitability of the product for their purpose prior to use. In accordance with good practices of personal cleanliness and hygiene, handle with due care and avoid unnecessary contact with this product.

B Safety Glasses Gloves



