Material Safety Data Sheet # 118	
For Printing Inks and related Materials	
OSHA Hazard Communication Standard, 29 CFR 1910.1200	

I. PRODUCT IDENTIFICATION		
Manufacturer: Gans Ink and Supply Co, Inc.	HMIS HAZARD IDENTIFICATION	
Address: 1441 Boyd Street		
Los Angeles, CA 90033		
	Health 1	
Emergency phone: (323) 264-2200	Flammability 1	
	Reactivity 1	
	Personal B	
	Protection	
Product Class: Lithographic Printing Ink	Manufacturer's code: Various, 011L, A106273,	
	F014861, A129457,	
	P428 OP, A140722	
Trade Name: Opaque white and Blends [Except 00-	38, 27994, (see MSDS Number 118.1)]	

II. HAZARDOUS INGREDIENTS

Material	CAS #	%	Exposure Limits	Units
Hydrotreated light	64742-55-8	5	OSHA TWA/PEL 5.0 mg/	/m3 ,mist
Paraffinic (petroleum) dist	tillates		OSHA/ STEL	NE
			ACGIH TLV/TWA 5.0 m	g/m3, mist
			ACGIH / STEL 10.0 mg	g/m3, mist
Diethylene glycol monohe	exyl ether 112-59-4		ACGIH TLV /TWA	NE
			ACGIH / STEL	NE
			OSHA /TWA	NE
			OSHA/ STEL	NE

III. HEALTH HAZARD INFORMATION

Effects of Overexposure Inhalation: This product is not expected to present an inhalation hazard at ambient conditions. Caution should be taken to prevent aerosolization or misting of this product. The threshold limit value (TLV) for this product as oil mist is 5 mg/ M^3 . Exposures below 5 mg/ M^3 appear to be without significant health risk. Acute overexposure may result in irritation of the throat and lungs. Chronic exposure to high concentrations of aerosols or mists to laboratory animals has resulted in non-specific symptoms related to the nervous system, gastrointestinal tract, and lungs. Skin Contact: Avoid skin contact. This product is non-irritating to the skin upon direct contact. Prolonged or repeated contact may result in contact dermatitis which is characterized by dryness, chapping, and reddening. This condition may make the skin more susceptible to other irritants, sensitizers, and disease. Pre-existing skin conditions may make the skin more susceptible and facilitate uptake by this route. Eye Contact: Avoid eye contact. This product may be slightly irritating to the eyes upon direct contact. This product has a low vapor pressure and is not expected to present a hazard to the eyes at ambient conditions. Exposure to high concentrations of vapors may be irritating to the eyes. Ingestion: Do not ingest. Ingestion of small quantities is usually nonfatal unless aspiration occurs. Severe oral intoxication will lead to intense burning of the throat and may result in drowsiness, dullness, numbness,

and headache followed by dizziness, weakness, and nausea. Loss of consciousness and convulsions followed by death may result. See *Notes to Physician* section below.

IV. FIRST AID PROCEDURES

Emergency & First Aid Procedures

Eyes: Immediately flush eyes with large amounts of water and continue flushing for 15 minutes until irritation subsides. Ensure adequate flushing of the eyes by separating the eyelids with fingers and roll eyes in a circular motion. If irritation persists, seek medical attention.

Skin: Remove contaminated clothing. Wash contaminated area thoroughly with soap and water. If redness or irritation occurs, seek medical attention. Launder contaminated clothing before reuse.

Inhalation: If mist or exposure is generated when the material is heated or handled, remove victim from exposure. If breathing has stopped or is irregular, administer artificial respiration and supply oxygen if it is available. If victim is unconscious, remove to fresh air and seek medical attention.

Ingestion: Do not induce vomiting. Seek immediate medical attention.

Notes to Physician: Aspiration may lead to chemical pneumonitis which is characterized by pulmonary edema and hemorrhage, and may be fatal. Signs of lung involvement include increased respiration rate, increased heart rate, and a bluish discoloration of the skin. Coughing, choking, and gagging are often noted at the time if aspiration. Gastrointestinal discomfort may develop, followed by vomiting, with risk of aspiration.

V. FIRE AND EXPLOSION DATA

Flash Point °F: > 200 F	Auto-ignition Temperature °F: No Data	
Flammable Limits in Air (%	Lower Limit: No Data	Upper Limit: No Data
Volume)		
Extinguishing Media: Use water fog, foam, CO ₂ , or dry chemical extinguishing media.		
Special Fire Fighting Procedures: Fire fighters use self-contained breathing apparatus and protective		
clothing. Water or water spray may be used to cool containers exposed to heat or flame.		
Unusual Fire & Explosion Hazard: Dense smoke may be generated while burning; carbon dioxide, carbon		
monoxide, and other oxides may be generated as products of combustion.		

VI. ACCIDENTAL RELEASE

Steps to be taken in event of spill or release: Absorb with an inert material such as vermiculite, sand, dirt, etc. Scrape up with trowel or scoop and place in a suitable container. Clean up with a suitable solvent.

VII. HANDLING AND STORAGE

Handling and Storage: Store in containers in a cool, well-ventilated area. Keep containers closed. Keep away from all sources of ignition, open flame, heat. Avoid prolonged contact with skin, contact with eyes, and breathing of mist or vapor. Always wash hands and face with soap and water before eating, drinking, and smoking.

Other Precautions: For industrial use only. Do not ingest. Consumption of food and beverages should be avoided in work areas where hydrocarbons are present. Always wash hands and face with soap and water before eating, drinking, and smoking.

VIII. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Ventilation Requirements: If vapor or mist is generated when the material is heated or handled, adequate ventilation in accordance with good engineering practice must be provided to maintain concentrations below the specific exposure or flammable limits.

Personal Protective Equipment

Respirator: Respiratory protection is not required under conditions of normal use. If vapor or mist is generated when the material is heated or handled, use an organic vapor respirator with a dust and mist filter. All respirators must be NIOSH certified. Do not use compressed oxygen in hydrocarbon atmospheres.

Skin: For prolonged exposures, use impervious synthetic chemical resistant rubber gloves

Eye: If material is handled such that it could be splashed into eyes, wear plastic face mask, face shield or splash-proof safety goggles.

IX. PHYSICAL AND CHEMICAL DATA

Boiling Range °F: 510-600	Vapor Density (Air = 1): < 1
Relative Density ($H_2O = 1$): 2.60 - 3.10	Vapor Pressure (mm Hg @ 68°F): 0.1
Material Density Lbs./Gal: 21.65 - 25.82	Solubility in Water: Insoluble
%Volatiles by Weight: < 5.0	% Solids by Weight: 95
VOC: lbs/gal: 1.29 g/L: 155.0	Appearance/Odor: White paste

X. STABILITY AND REACTIVITY INFORMATION

Stability (Thermal, Light, etc.): Stable	Conditions to avoid: Excessive heat, sources of	
	ignition and open flame.	
Hazardous Polymerization: Will not occur.	Materials to avoid: Contact with strong oxidizers.	
Hazardous Decomposition Products: CO ₂ , CO, and other oxides may be generated as products of		
combustion.		

XI. TOXICOLOGICAL INFORMATION

CARCINOGEN: This product has not been identified as a carcinogen by OSHA or the National
Toxicology Program (NTP), or the International Agency for Research Cancer (IARC).Mutagen:No DataTeratogen:No DataReproductive Toxicity:No Data

No toxicity studies have been conducted on this product.

As with all chemicals for which test data are limited or do not exist, caution must be exercised through the prudent use of protective equipment and handling procedures to minimize exposure.

XII. ECOLOGICAL INFORMATION

This product has not been evaluated at this time. Do not allow to enter waterways, sewers or drains.

XIII. DISPOSAL INFORMATION

Waste Disposal Method: If recycling as ink is not possible, material may be incinerated or land filled at a licensed facility in accordance with local, state, and federal regulations. Do not allow to enter sewers, drains, waterways etc.

XIV. TRANSPORT INFORMATION

Flammability Classification:	Combustible Liquid
OSHA:	Class III B
DOT:	Not Regulated

XV. REGULATORY INFORMATION

SARA Title III Section 313:This material may contain chemicals subject to the reporting requirements of the SARA SuperfundAmendments and Reauthorization Act.Cobalt tallate61789-52-4trace amountsManganese comp. Glycol Ethers,

112-59-4

U.S. CERCLA SARA Title III Section 312 Hazard Category: (40 CFR 311/312):

Not Hazardous

Diethylene glycol monohexyl ether

TSCA Section 8(b) Inventory Status:

All component(s) of this product are either exempt or listed on the TSCA Inventory.

Canadian Domestic Substances List (DSL):

Canadian DSL: One or more components are listed on the NDSL

U.S. State Regulations

California Proposition 65:

This product contains a chemical known by the state of California to cause cancer and/or reproductive harm.

Benzene 71-43-2 Trace amount

XVI. OTHER INFORMATION

The information herein is presented in good faith, based on the data available to us and is believed to be correct as of the date hereof. However, Gans Ink and Supply Co., Inc. makes no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Gans Ink and Supply Co., Inc. assumes no responsibility for any damages of any nature directly or indirectly resulting from the use of or reliance upon the information contained herein. Users must make their own determination as to the suitability of the product for their purpose prior to use. In accordance with good practices of personal cleanliness and hygiene, handle with due care and avoid unnecessary contact with this product.