Material Safety Data Sheet #125

For Printing Inks and related Materials
OSHA Hazard Communication Standard, 29 CFR 1910.1200

Date of preparation: 6-3-2010 MSDS#: 125

I. PRODUCT IDENTIFICATION

Manufacturer: Gans Ink and Supply Co, Inc.	HMIS HAZARD IDENTIFICATION	
Address: 1441 Boyd Street		
Los Angeles, CA 90033		
	Health 1	
Emergency phone: (323) 264-2200	Flammability 0	
	Reactivity 0	
	Personal C	
	Protection	
Product Class: Aqueous Gloss Coating	Manufacturer's code: S-1881 D	
Trade Name: WB Gloss Coating, H/R 220		

II. HAZARDOUS INGREDIENTS

II: III III III III III III III III III				
Material	CAS#	%	Exposure Limits	Units
Sodium Dioctylsulfosccinate	577-11-7	1 - 3	OSHA / PEL ACGIH TLV/TWA ACGIH / STEL	Not Established Not Established Not Established
Ammonium Hydroxide	1336-21-6	0 – 1	OSHA / PEL ACGIH TLV/ TWA ACGIH / STEL	50 ppm 25 ppm 35 ppm

The amount of Ammonium Hydroxide reported in Section II is calculated to be the excess neutralizer after creation of the polymer solution.

III. HEALTH HAZARD INFORMATION

Effects of Overexposure

Inhalation: Inhalation is an unlikely route of exposure under conditions of intended use. Higher temperatures may generate vapors that may cause irritation of the eyes and respiratory tract. Acute overexposure may result in irritation of the throat and lungs.

No chronic health hazards are associated with the components present in this product.

Skin Contact: Avoid skin contact. Skin contact is expected to be the primary route of occupational exposure. Prolonged or repeated contact with skin may cause mild irritation. Symptoms may include stinging, tearing, redness, swelling and / or burning. This condition may make the skin more susceptible to other irritants, sensitizers, and disease. Pre-existing skin conditions may make the skin more susceptible and facilitate uptake by this route.

Eye Contact: Avoid eye contact. This product may be mildly irritating to the eyes upon direct contact. Symptoms may include stinging, tearing, redness, swelling and / or burning. Higher temperatures may generate vapors that may cause irritation to the eyes. Exposure to high concentrations of vapors may be irritating to the eyes.

Ingestion: Do not ingest. Ingestion is an unlikely route of exposure under conditions of intended use. Deliberate ingestion of excessive quantities may be harmful. Ingestion of small quantities is usually nonfatal unless aspiration occurs. Severe oral intoxication will lead to intense burning of the throat and may result in drowsiness, dullness, numbness, and headache followed by dizziness, weakness, and nausea. Loss

of consciousness and convulsions followed by death may result. See Notes to Physician section below.

IV. FIRST AID PROCEDURES

Emergency & First Aid Procedures

Eyes: Immediately flush eyes with large amounts of water and continue flushing for 15 minutes, lifting upper and lower lids occasionally. If irritation or redness persists, seek immediate medical attention.

Skin: Remove contaminated clothing. Wash contaminated area thoroughly with soap and water. Solvents should not be used to clean skin because of increased penetration potential. If redness or irritation occurs, seek immediate medical attention. Wash clothing and thoroughly clean shoes before reuse.

Inhalation: Remove to fresh air. If breathing has stopped or is irregular, administer artificial respiration and supply oxygen if it is available. Seek immediate medical attention.

Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth and then drink plenty of water. Seek immediate medical attention.

Notes to Physician: Aspiration may lead to chemical pneumonitis which is characterized by pulmonary edema and hemorrhage, and may be fatal. Signs of lung involvement include increased respiration rate, increased heart rate, and a bluish discoloration of the skin. Coughing, choking, and gagging are often noted at the time if aspiration. Gastrointestinal discomfort may develop, followed by vomiting, with risk of aspiration. Treat according to symptoms (decontamination, vital functions), no known specific antidote.

V. FIRE AND EXPLOSION DATA

Flash Point °F: > 200 F (Closed Cup)		Auto-ignition Temperature °F: No Data	
Flammable Limits in Air (%	Lower Limit: N	lo Data	Upper Limit: no Data
Volume)			

Extinguishing Media: Use water spray, foam, or dry chemical extinguishing media.

Special Fire Fighting Procedures: The use of self contained breathing apparatus is recommended for firefighters. Cool containers and use caution when approaching or handling fire- exposed containers. **Unusual Fire & Explosion Hazard:** Dense smoke may be generated while burning; carbon dioxide, carbon monoxide, and other oxides of nitrogen and sulfur may be generated as products of combustion. The container may burn and leak in the heat of a fire.

VI. ACCIDENTAL RELEASE

Steps to be taken in event of spill or release: Keep unnecessary personnel away from spill area. Use appropriate personal protective equipment such as chemical resistant apron, impervious gloves and face shield if splash hazard exists. Soak up small spill with inert material such as vermiculite, sand, dirt etc. For large spills dike area. Scrape up with trowel or scoop and place in a suitable container. Clean up with a strong detergent and water. Keep all materials out of drains, sewers and waterways.

VII. HANDLING AND STORAGE

Handling and Storage: Store in containers in a cool, well-ventilated area. Use and store products with adequate room ventilation. It is recommended that containers of these products be stored at temperatures between $40 \, \text{F}$ and $115 \, \text{F}$ ($4.5 \, \text{C} - 45 \, \text{C}$). The slight ammonia smell can become stronger if the coating will be heated higher than room temperature. Protect from freezing. Take precautionary measures against static discharges. Avoid prolonged contact with skin, contact with eyes, and breathing of mist or vapor. Use impervious gloves, chemical resistant apron and eye protection (full face shield if splashing hazard exists) when handling.

Other Precautions: For industrial use only. Do not ingest. Consumption of food and beverages should be avoided in work areas where hydrocarbons are present. Always wash hands and face with soap and water before eating, drinking, and smoking. Avoid prolonged contact with skin, contact with eyes, and breathing of mist or vapor.

VIII. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Ventilation Requirements: If vapor or mist is generated when the material is heated or handled, adequate ventilation in accordance with good engineering practice must be provided to maintain concentrations below the specific exposure or flammable limits.

Personal Protective Equipment

Respirator: Respiratory protection is not required under conditions of normal use. If vapor or mist is generated when the material is heated or handled, use an organic vapor respirator with a dust and mist filter. All respirators must be NIOSH certified. Do not use compressed oxygen in hydrocarbon atmospheres.

Skin: Use impervious gloves when handling. Use a chemical resistant apron. Provide readily accessible safety showers

Eye: Eye protection is required under conditions of normal use. Safety glasses, full face shield or chemical safety goggles are recommended to prevent eye contact. Eye protection should meet the specifications of ANSI Z87.1 Provide readily accessible eye wash stations.

IX. PHYSICAL AND CHEMICAL DATA

Boiling Range ° F : 212 F	Vapor Density (Air = 1): Not available
Relative Density ($H_2O = 1$): 1.045	Vapor Pressure (mm Hg @ 70°F): No Data
Material Density Lbs./Gal: 8.70	Solubility in Water: Soluble
% Volatile Organic Compounds (VOC) by	Evaporation Rate: Not Available
Weight: 4.2	pH: 8.7 ± 0.7
VOC: lbs/gal: 0.36 g/L: 43.9	Appearance/Odor: Milky white liquid/ slight
	Ammonia odor

X. STABILITY AND REACTIVITY INFORMATION

IN STIBILITY IN IS INSTITUTE IN STRUCTURE		
Stability (Thermal, Light, etc.): Normally stable	Conditions to avoid: Excessive heat (< 140 F) and	
under conditions of storage and intended use.	sources of ignition. Avoid storage below 40 F (4.5C)	
	and above 115 F (45C)	
Hazardous Polymerization: Will not occur.	Materials to avoid: Keep away from strong acids.	
Hazardous Decomposition Products: Smoke, CO ₂ , CO, and other oxides of nitrogen may be generated as		
products of combustion.		

XI. TOXICOLOGICAL INFORMATION

CARCINOGEN: This product contains no listed carcinogens according to OSHA, ACGIH, the National Toxicology Program (NTP), or the International Agency for Research Cancer (IARC) in concentrations of 0.1 percent or greater.

Mutagen:No DataTeratogen:No DataReproductive Toxicity:No Data

Information pertaining to the health effects and toxicity of the "pure" form of the hazardous components identified in Section II is presented below. This information reflects the known hazards associated with the component and may not reflect that of the purchased material due to concentration (dilution) effects Review and interpretation by your Hazard Communication Department is recommended.

Sodium Dioctylsulfosuccinate

Oral: LD50: 1900 mg/kg (rat)
Draize Test, Skin: 10 mg/24 H Moderate (rabbit)

Draize Test, Eye: 1 % Severe (rabbit)
Inhalation: No information available

Ammonium Hydroxide

Oral: LD50: 350 mg/kg (rat)
Skin Irritant: Severe irritant (rabbit)
Eye Irritant: Severe irritant (rabbit)

Carcinogenicity: Not listed by ACGIH, IARC, NIOSH, NTP, or OSHA.

XII. ECOLOGICAL INFORMATION

Information pertaining to the ecological fate of the "pure" form of the hazardous components identified in Section II is presented below. This information reflects the known hazards associated with the component

and may not reflect that of the purchased material due to concentration (dilution) effects Review and interpretation by your Hazard Communication Department is recommended.

Sodium Dioctylsulfosuccinate

No Information available.

Ammonium Hydroxide

Fish: Rainbow trout: LC50: 0.008 mg/L; 24hr Fish: Fathead minnow: LC50: 8.2 mg/L; 24 hr Water Flea: Daphnia: EC50: 0.66 mg/L: 48 hr

XIII. DISPOSAL INFORMATION

Waste Disposal Method: If recycling as ink is not possible, material may be incinerated or land filled at a licensed facility in accordance with local, state, and federal regulations.

Since empty containers may retain product residues, all hazard precautions given in this data sheet should be observed.

Do not allow to enter sewers, drains or waterways.

XIV. TRANSPORT INFORMATION

Flammability Classification:

OSHA: Class III B

US DOT Proper Ship Name (ground): Resin compounds, liquid

Class: Not applicable UN ID Not applicable Packing Group: Not applicable

IMDG Proper Ship Name (ocean): Resin compounds, liquid

Class: Not applicable UN ID Not applicable Packing Group: Not applicable

ICAO/ IATA Proper Ship Name (air): Resin compounds, liquid

Class: Not applicable
UN ID Not applicable
Packing Group: Not applicable

TDG Proper Ship Name (ground): Resin compounds, liquid

Class: Not applicable
UN ID Not applicable
Packing Group: Not applicable

XV. REGULATORY INFORMATION

EPA SARA Title III Section 313 (40 CFR 372) Component (s) above 'de minimus' level:

This product contains the following chemicals in quantities which must be reported under the supplier notification requirements of Section 313 of the Emergency Planning and Community Right- To- Know Act of 1986:

Chemical NameCAS NumberAmmonium Hydroxide1336-21-6

CERCLA Reportable Quantities

Components present which could require reporting under CERCLA 40 CFR 302.4

Chemical NameCAS NumberCERCLA RQAmmonium Hydroxide1336-21-61000 LBS

TSCA Section 8(b) Inventory Status:

All component(s) of this product are either exempt or listed on the TSCA Inventory.

U.S. State Regulations

California Proposition 65:

This product does not intentionally contain any chemicals known by the state of California to cause cancer and/or reproductive harm. Moreover, Gans Ink and Supply Co., Inc. does not routinely analyze its products for impurities which may be such chemicals.

Clean Air Act Amendment (HAPs)

This product does not contain any chemicals which are defined as Hazardous Air Pollutants under Title III of the Clean Air Act Amendments of 1990.

Coalition of Northeast Governors (CONEG) Legislation:

This product is certified to be in full compliance with CONEG Model Toxic Legislation for packaging and packaging components.

Canadian WHMIS Classification

Components present in the WHMIS hazardous ingredient disclosure list.

Chemical Name	CAS Number
Ammonium Hydroxide	1336-21-6 577-11-7
Sodium Dioctylsulfosuccinate	3//-11-/

XVI. OTHER INFORMATION

The information herein is presented in good faith, based on the data available to us and is believed to be correct as of the date hereof. However, Gans Ink and Supply Co., Inc. makes no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Gans Ink and Supply Co., Inc. assumes no responsibility for any damages of any nature directly or indirectly resulting from the use of or reliance upon the information contained herein. Users must make their own determination as to the suitability of the product for their purpose prior to use. In accordance with good practices of personal cleanliness and hygiene, handle with due care and avoid unnecessary contact with this product.

	Health	Fire	Reactivity
Suggested NFPA Rating	1	0	0
Suggested HMIS Rating	1	0	0