

I. PRODUCT IDENTIFICATION

Manufacturer: Gans Ink and Supply Co, Inc. Address: 1441 Boyd Street Los Angeles, CA 90033 Emergency phone: (323) 264-2200	<p align="center">HMIS HAZARD IDENTIFICATION</p> <table border="1"> <tr> <td>Health</td> <td>2</td> </tr> <tr> <td>Flammability</td> <td>1</td> </tr> <tr> <td>Reactivity</td> <td>2</td> </tr> <tr> <td>Personal Protection</td> <td>B</td> </tr> </table>	Health	2	Flammability	1	Reactivity	2	Personal Protection	B
Health	2								
Flammability	1								
Reactivity	2								
Personal Protection	B								
Product Class: Lithographic UV Printing Ink	Manufacturer's code: Various, UV14660, X102516, X103174, UV11991-4, UV15127, UV15265 to UV15268 (Test), X102686, UVR001, UVR002, UVR003, UVR004, UVR005, UVR006, UVR007, UVR008, UVR009, UVR010, UVR011, UVR012, UVR013, UVD001, UVD002, UVD003, UVD004, UVD005, UVD006, UVD007, UVD008, UVD009, UVD010, UVD011, UVD012, UVD013, UV15709, UV15710, UV15712								
Trade Name: Rapicure, Rapicure F/R, UV High Speed Web (inc. the 9000 and 9010 blending bases), HUV-2 Process (Tests), Dry Cure Pantone Blend									

II. HAZARDOUS INGREDIENTS

Material	CAS #	%	Exposure Limits	Units
Acrylate mixtures	Not available	4-31	Not Established	
Resin mixtures	Not available	0-6	Not Established	
Photoinitiator mixtures	Not available	3-4	ACGIH PEL	5 mg/M ³

III. HEALTH HAZARD INFORMATION

Effects of Overexposure
Inhalation: Not expected to be a hazard due to low volatility under standard conditions. Inhalation of mist or vapor may cause irritation or respiratory tract.
Skin Contact: No specific information available. Contains materials that may cause moderate skin injury (reddening and swelling) and/or sensitization. Prolonged contact may cause blister formations (burns). Since irritation may not occur immediately, contact can go unnoticed.
Eye Contact: Moderate irritant. Can cause burning sensation, tearing, swelling, and redness. Injury may persist for several days.
Ingestion: May irritate the mouth, throat, and gastrointestinal tract.

IV. FIRST AID PROCEDURES

Emergency & First Aid Procedures
Eyes: Immediately flush eyes with large amounts of water and continue flushing for 15 minutes until irritation subsides. If irritation persists, seek medical attention.
Skin: Remove contaminated clothing. Wash contaminated area thoroughly with soap and water. If redness or irritation occurs, seek medical attention.
Inhalation: This material has a low vapor pressure and is not expected to present an inhalation exposure at

ambient conditions. If mist or exposure is generated when the material is heated or handle, remove victim from exposure. If breathing has stopped or is irregular, administer artificial respiration and supply oxygen if it is available. If victim is unconscious, remove to fresh air and seek medical attention.

Ingestion: Do not induce vomiting. Seek immediate medical attention.

Notes to Physician: Aspiration may lead to chemical pneumonitis which is characterized by pulmonary edema and hemorrhage, and may be fatal. Signs of lung involvement include increased respiration rate, increased heart rate, and a bluish discoloration of the skin. Coughing, choking, and gagging are often noted at the time if aspiration. Gastrointestinal discomfort may develop, followed by vomiting, with risk of aspiration.

V. FIRE AND EXPLOSION DATA

Flash Point °F: > 200	Auto-ignition Temperature °F: No Data	
Flammable Limits in Air	Lower Limit: No Data	Upper Limit: No Data
Extinguishing Media: Use water fog, foam, CO ₂ , or dry chemical extinguishing media.		
Special Fire Fighting Procedures: Remove all ignition sources. Wear self-contained breathing apparatus and complete personal protective equipment when entering confined areas.		
Unusual Fire & Explosion Hazard: High temperatures and fire conditions may cause rapid and uncontrollable polymerization which can result in explosions and the violent rupture of storage vessels. Avoid the use of a stream of water to control fires since frothing can occur.		

VI. ACCIDENTAL RELEASE

Steps to be taken in event of spill or release: Remove all ignition sources, as spilled material may polymerize. Move leaking containers to ventilated area. Stop discharge, if it can be performed safely, and contain material. Place in a suitable container for disposal. **Do NOT** flush to sewer.

VII. HANDLING AND STORAGE

Handling and Storage: Store in containers in a cool, well-ventilated area. Avoid prolonged contact with skin, contact with eyes, and breathing of mist or vapor. Avoid all sources of heat and ignition. Avoid direct sunlight and UV light..

Other Precautions: For industrial use only. Do not ingest. Consumption of food and beverages should be avoided in work areas where hydrocarbons are present. Always wash hands and face with soap and water before eating, drinking, and smoking.

VIII. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Ventilation Requirements: If vapor or mist is generated when the material is heated or handled, adequate ventilation in accordance with good engineering practice must be provided to maintain concentrations below the specific exposure or flammable limits.

Personal Protective Equipment

Respirator: Respiratory protection is not required under conditions of normal use. If vapor or mist is generated when the material is heated or handled, use an organic vapor respirator with a dust and mist filter. All respirators must be NIOSH certified. Do not use compressed oxygen in hydrocarbon atmospheres.

Skin: For prolonged exposures, use impervious synthetic rubber clothing (boots, gloves, etc.) over parts of the body subject to exposure. Individuals with pre-existing skin disorders can be at greater risk. Those known to be sensitized to Acrylate should avoid all exposure to this product. Safety showers are recommended.

Eye: If material is handled such that it could be splashed into eyes, wear plastic face shield or splash-proof safety glasses or goggles. Individuals with pre-existing eye disorders can be at greater risk. Those known to be sensitized to Acrylate should avoid all exposure to this product. Eyewash wash stations are recommended.

IX. PHYSICAL AND CHEMICAL DATA

Boiling Range °F: > 200 F	Vapor Density (Air = 1): > 1
Relative Density (H₂O = 1): 0.95 – 1.15	Vapor Pressure (mm Hg @ 68°F): Slower than Butyl Acetate
Material Density Lbs./Gal: 7.91 – 9.58	Solubility in Water: Insoluble

% Volatiles by Weight: <1	% Solids by Weight: 99 - 100
VOC: lbs/gal: < 0.096 g/L: 11.5	Appearance/Odor: Colored paste

X. STABILITY AND REACTIVITY INFORMATION

Stability (Thermal, Light, etc.): Stable	Conditions to avoid: Do Not store above 140°F. Avoid exposure to ultra violet and /or sunlight.
Hazardous Polymerization: High temperatures (>140°F) and oxygen deficient atmosphere reduce effectiveness and may cause polymerization, raising the temperature and pressure, possible rupturing the container. Do NOT blanket or mix with nitrogen or other inert gases as this renders the inhibitor ineffective.	Materials to avoid: Initiators including peroxides, strong oxidizing agents, copper, copper alloys, carbon steel, iron, rust, nickel, cobalt and strong bases.
Hazardous Decomposition Products: Carbon monoxide, Carbon dioxide and other oxides may be generated as products of combustion.	

XI. TOXICOLOGICAL INFORMATION

CARCINOGEN: This product has not been identified as a carcinogen by OSHA or the National Toxicology Program (NTP), or the International Agency for Research Cancer (IARC).	
Mutagen:	No Data
Teratogen:	No Data
Reproductive Toxicity:	No Data

XII. ECOLOGICAL INFORMATION

This product has not been evaluated at this time. As with all chemicals and products do not allow to enter drains, sewers or waterways.

XIII. DISPOSAL INFORMATION

Waste Disposal Method: If discarded in its original unused form, this product Does NOT exhibit the characteristics of a RCRA hazardous waste as defined under 40CFR261. Waste materials should be dumped or buried in an approved landfill, or incinerated in a suitable combustion chamber. Disposal must comply with all local, state, and federal regulations. Of the methods of disposal currently available, it is recommended that an alternative be selected according to the following order of preference, based upon environmental acceptability: 1) Recycle or rework if at all feasible. 2) Incinerate at an authorized facility. 3) Treat at an acceptable waste treatment facility.
--

XIV. TRANSPORT INFORMATION

Flammability Classification:	
OSHA:	Class III B
DOT (Ground):	Not Regulated

XV. REGULATORY INFORMATION

U.S. Federal Regulations SARA Superfund Amendments and Reauthorization Act of 1986 Title III Section 313: This product does not contain any component(s) listed on the Section 313 Toxic Chemical List. (40 CFR 372.65). HAP Clean Air Act - Hazardous Air Pollutants This product does not contain any HAP, as defined by the U.S. Clean Air Act Section 112 (40 CFR 61)
--

Clean Water Act:

None of the chemicals in this product are listed as Priority Pollutants under the CWA.

Section 302 – Extremely hazardous substances: This product does not contain any components regulated under Section 302 (40 CFR 355) as EHS.

Section 311/312 – Hazard Categories: Pursuant to Section 311/312 of SARA Title III, the physical and health hazard categories for this product are identified below:

- Fire Hazard – NO
- Sudden Release of Pressure Hazard – NO
- Reactivity Hazard – YES
- Immediate (acute) Health Hazard – YES
- Delayed (chronic) Health Hazard – YES.

CONEG: Coalition of Northeast Governors: This product meets the Coalition of Northeast Governors (CONEG) Source Reduction Council limits for the sum of the levels of Lead, Cadmium, Mercury and Hexavalent Chromium of less than 100 parts per million by weight.

TSCA Section 8(b) Inventory Status:

All component(s) of this product are either exempt or listed on the TSCA Inventory.

U.S. State Regulations

California Proposition 65:

This product does not intentionally contain any chemicals known by the state of California to cause cancer and/or reproductive harm. Moreover, Gans Ink and Supply Co., Inc. does not routinely analyze its products for impurities which may be such chemicals.

International Regulations

Reduction of Hazardous Substances (RoHS) Compliance:

Directive 2002/95/EC of the European Parliament and of the Council of the European Union - Reduction of Hazardous Substances (RoHS) Compliance.

XVI. OTHER INFORMATION

The information herein is presented in good faith, based on the data available to us and is believed to be correct as of the date hereof. However, Gans Ink and Supply Co., Inc. makes no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Gans Ink and Supply Co., Inc. assumes no responsibility for any damages of any nature directly or indirectly resulting from the use of or reliance upon the information contained herein. Users must make their own determination as to the suitability of the product for their purpose prior to use. In accordance with good practices of personal cleanliness and hygiene, handle with due care and avoid unnecessary contact with this product.

B

Safety Glasses
Gloves

