

Material Safety Data Sheet # 275
For Printing Inks and related Materials
OSHA Hazard Communication Standard, 29 CFR 1910.1200

Date of preparation: 5-12-09
 Updated: 10/22/2013
 Supersedes: 5/10/2012
 MSDS#: 275

I. PRODUCT IDENTIFICATION

Manufacturer: Gans Ink and Supply Co, Inc. Address: 1441 Boyd Street Los Angeles, CA 90033 Emergency phone: (323) 264-2200	HMIS HAZARD IDENTIFICATION								
	<table border="1"> <tr><td>Health</td><td>2</td></tr> <tr><td>Flammability</td><td>0</td></tr> <tr><td>Reactivity</td><td>1</td></tr> <tr><td>Personal Protection</td><td>B</td></tr> </table>	Health	2	Flammability	0	Reactivity	1	Personal Protection	B
Health	2								
Flammability	0								
Reactivity	1								
Personal Protection	B								
Product Class: UV Screen Coating	Manufacturer's code: UVS- 4703, UVS- 4703HV								
Trade Name: Lustre Glo Gloss UV Screen									

II. HAZARDOUS INGREDIENTS

Material	CAS #	%	Exposure Limits	Units
(1-methyl-1,2ethanediyl)bis[oxymethyl-2,1-ethanediyl]diacrylate	42978-66-5 EINECS 256-032-2	10 - 29.9	OSHA/ PEL Xi; R36/37/38. N;R51/53, R43	NE
Epoxy Acrylate	55818-57-0 EINECS 500-130-2	30 - 60	OSHA/ PEL	NE
Benzophenone	119-61-9 EINECS 200-337-6	2 - 5	OSHA	NE

Symbols: NE: Not Established
 Xi: Irritant
 R43: May cause sensitization
 R52/53: Harmful to aquatic organisms. May cause long- term adverse effects in the aquatic environment.
 R36/37/38: Irritating to eyes, respiratory tract and skin.

III. HEALTH HAZARD INFORMATION

Effects of Overexposure
Inhalation: Avoid inhalation. Inhalation of mist or vapor may cause irritation of respiratory tract. Irritating to mucous membranes. Acute overexposure may result in irritation of the throat and lungs.
Skin Contact: Avoid skin contact. This product is irritating to the skin upon direct contact. Prolonged or repeated contact may result in contact dermatitis which is characterized by dryness, chapping, and reddening. This condition may make the skin more susceptible to other irritants, sensitizers, and disease. Pre-existing skin conditions may make the skin more susceptible and facilitate uptake by this route.
Eye Contact: Avoid eye contact. Moderate irritant. This product is irritating to the eyes upon direct contact. Can cause burning sensation, tearing, swelling, and redness. Injury may persist for several days. Those known to be sensitized to acrylates should avoid all exposure to this product.
Ingestion: Do not ingest. May irritate the mouth, throat, and gastrointestinal tract. Severe oral intoxication will lead to intense burning of the throat and may result in drowsiness, dullness, numbness, and headache followed by dizziness, weakness, and nausea. See <i>Notes to Physician</i> section below.

IV. FIRST AID PROCEDURES

Emergency & First Aid Procedures
Eyes: Immediately flush eyes with large amounts of water and continue flushing for 15 minutes until irritation subsides. Seek medical attention. If wearing contact lenses, remove before rinsing eyes.
Skin: Remove contaminated clothing. Wash contaminated area thoroughly with soap and cold water immediately. If redness or irritation occurs, seek medical attention. Launder contaminated clothing before reuse.
Inhalation: Remove victim from exposure. If breathing has stopped or is irregular, administer artificial respiration and supply oxygen if it is available. If victim is unconscious, remove to fresh air and seek medical attention.
Ingestion: Do not induce vomiting. If vomiting should occur spontaneously keep airway clear. Seek immediate medical attention. Never give anything by mouth to an unconscious person.
Notes to Physician: Aspiration may lead to chemical pneumonitis which is characterized by pulmonary edema and hemorrhage, and may be fatal. Signs of lung involvement include increased respiration rate, increased heart rate, and a bluish discoloration of the skin. Coughing, choking, and gagging are often noted at the time of aspiration. Gastrointestinal discomfort may develop, followed by vomiting, with risk of aspiration.

V. FIRE AND EXPLOSION DATA

Flash Point °F: 212 F (Cleveland open cup)	Auto-ignition Temperature °F: No Data	
Flammable Limits in Air (% Volume)	Lower Limit: No Data	Upper Limit: No Data
Extinguishing Media: Use water spray fog or mist, foam, CO ₂ , or dry chemical extinguishing media.		
Special Fire Fighting Procedures: Remove all ignition sources. Fire fighters should wear self-contained breathing apparatus and complete personal protective equipment when entering buildings and confined areas where this material is stored. Keep containers cool by spraying with water if exposed to fire. Product may polymerize at high temperatures. Polymerization is a highly exothermic reaction and may produce sufficient heat to cause thermal decomposition and / or rupture of container. Move container from fire area if it can be done safely.		
Unusual Fire & Explosion Hazard: High temperatures and fire conditions may cause rapid and uncontrollable polymerization which can result in explosions and the violent rupture of storage vessels. Uncontrolled polymerization may occur at temperatures above 140F (60C).		

VI. ACCIDENTAL RELEASE

Steps to be taken in event of spill or release: Remove all ignition sources, as spilled material may polymerize. Move leaking containers to ventilated area. Stop discharge, if it can be performed safely. Absorb product with a suitable material such as vermiculite, cloth or sawdust. Place in a suitable container for disposal. Dispose of in accordance with state, local and Federal regulations. Do NOT flush to sewers, drains or waterways. Clean up with a suitable solvent.
--

VII. HANDLING AND STORAGE

Handling and Storage: Store in closed containers in a cool, well-ventilated area. DO NOT expose to direct sunlight, ultraviolet light or temperatures exceeding 140 F (60C) as it may cause uncontrollable polymerization of this product with generation of heat. Keep away from all sources of heat, open flame, and sources of ignition. Keep from freezing. Avoid prolonged contact with skin, contact with eyes, and breathing of mist or vapor. Always wash hands and face with soap and water before eating, drinking, and smoking. Avoid discharge into the environment
Other Precautions: For industrial use only. Do not ingest. Consumption of food and beverages should be avoided in work areas. Avoid prolonged contact with skin, contact with eyes, and breathing of mist or vapor.

VIII. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Ventilation Requirements: Local exhaust is recommended. Adequate ventilation in accordance with good engineering practice must be provided to maintain concentrations below the specific exposure or flammable

limits.
Personal Protective Equipment
Respirator: Respiratory protection is not required under conditions of normal use. If vapor or mist is generated when the material is heated or handled, use an organic vapor respirator with a dust and mist filter. All respirators must be NIOSH certified. Do not use compressed oxygen in hydrocarbon atmospheres.
Skin: The use of impervious protective clothing (boots, gloves, aprons etc.) over parts of the body subject to exposure is recommended. DO NOT wear PVC gloves as PVC absorbs Acrylate.
Eye: The use of eye protection is recommended. Wear plastic face shield or splash-proof safety glasses or goggles. Eye wash stations are recommended.

IX. PHYSICAL AND CHEMICAL DATA

Boiling Point °F: > 200 °F	Vapor Density (Air = 1): No Data
Relative Density (H₂O = 1): 0.985	Vapor Pressure (mm Hg @ 68°F): < 1
Material Density Lbs./Gal: 8.20	Solubility in Water: Insoluble
%Volatiles by Weight: 0	pH: N/o Data
VOC: lbs/gal: 0 g/L: 0	Appearance/Odor: Colorless liquid / Acrylic odor

X. STABILITY AND REACTIVITY INFORMATION

Stability (Thermal, Light, etc.): Stable under conditions of intended use.	Conditions to avoid: Avoid excessive heat, temperatures above 140 °F (60°C). Keep from freezing. Keep away from open flame, heat, and sources of ignition. Avoid direct sunlight and ultraviolet light.
Hazardous Polymerization: Hazardous exothermic polymerization can occur when heated, or when exposed to direct sunlight.	Materials to avoid: Contact with strong oxidizers, free radical producing initiators, peroxides and metal ions or alloys.
Hazardous Decomposition Products: None	

XI. TOXICOLOGICAL INFORMATION

CARCINOGEN: This product has not been identified as a carcinogen by OSHA or the National Toxicology Program (NTP), or the International Agency for Research Cancer (IARC).	
Mutagen:	No Data
Teratogen:	No Data
Reproductive Toxicity:	No Data
The toxicological properties are not fully determined.	

XII. ECOLOGICAL INFORMATION

Harmful to aquatic organisms. May cause long- term adverse effects in the aquatic environment. Do Not allow to enter sewers, waterways, drains etc.

XIII. DISPOSAL INFORMATION

Waste Disposal Method: If recycling as ink is not possible, material may be incinerated or land filled at a licensed facility in accordance with local, state, and federal regulations. Do not allow to enter sewers, drains or waterways.

XIV. TRANSPORT INFORMATION

Flammability Classification:	
OSHA:	Class III B
US DOT (Ground):	
Proper Shipping Name:	Not Regulated
Hazard Class:	None
Packing Group:	None
ADR/ RID:	Not Applicable

IMO/ IMDG (Sea):
Proper Shipping Name: Environmentally hazardous substance, liquid, n.o.s.
Hazard class or division: 9

ICAO/ IATA (Air):
Proper Shipping Name: Environmentally hazardous substance, liquid, n.o.s.
Hazard class or division: 9

XV. REGULATORY INFORMATION

SARA Title III Section 313:
This material DOES NOT contain chemicals subject to the reporting requirements of the SARA Superfund Amendments and Reauthorization Act.

SARA (Superfund Amendments and Reauthorization Act of 1986) Title III:
SARA Section 302 - Extremely Hazardous Substances (EHS):

This product does not contain any components regulated under Section 302 (40 CFR 355) as EHS.

TSCA Section 8(b) Inventory Status:
All component(s) of this product are either exempt or listed on the TSCA Inventory.

TSCA 12(b) Export Notification:
This product does not contain any component(s) that are subject to a Section 12(b) Export Notification.

U.S. State Regulations

California Proposition 65:
This product contains a chemical(s) known by the state of California to cause cancer.

<u>Chemical</u>	<u>CAS#</u>
Benzophenone	119-61-9

XVI. OTHER INFORMATION

The information herein is presented in good faith, based on the data available to us and is believed to be correct as of the date hereof. However, Gans Ink and Supply Co., Inc. makes no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Gans Ink and Supply Co., Inc. assumes no responsibility for any damages of any nature directly or indirectly resulting from the use of or reliance upon the information contained herein. Users must make their own determination as to the suitability of the product for their purpose prior to use. In accordance with good practices of personal cleanliness and hygiene, handle with due care and avoid unnecessary contact with this product.

B

Safety Glasses
Gloves

