

Product Name: SS21 ink Black SDS No. 037-S080496 First issue: 2007/07/31

Revised: 2015/06/15

#### 1. Identification

Product Name : SS21 ink Black

Order No. : SPC-0501K-2 / SPC-0588K-2

General Use : Ink for ink jet printer
Product Description : Solvent pigment ink

SDS Number : 037-S080496

Manufacture

Company Name : Mimaki Engineering Co., Ltd.

Address : 2182-3 Shigeno-otsu, Tomi-shi, Nagano 389-0512 JAPAN

Telephone No. : +81-268-64-2413

Importer / Distributor Established in USA

Company Name : MIMAKI USA, INC.

Address : 150 Satellite Boulevard, suite A, Suwanee, Georgia 30024, U.S.A.

Telephone No. : +1-678-730-0100 Emergency Telephone No. : +81-268-64-2281

#### 2. Hazards Identification

[GHS Classification]

Physical Hazards

Flammable Liquids : Category 4

Health Hazards

Acute Toxicity – Oral : Category 4 (80-90% unknown)

Eye Damage / Irritation : Category 2
Carcinogenicity : Category 2

Specific Target Organ Toxicity : Category 2 (central nervous system)

(Single Exposure)

Specific Target Organ Toxicity : Category 1 (lungs)

(Repeated Exposure)

**Environmental Hazards** 

Hazardous to the Aquatic : Category 3

Environment - Acute Hazard

The above list does not include category being non-classifiable or not-applicable.



Product Name: SS21 ink Black SDS No. 037-S080496 First issue: 2007/07/31

Revised: 2015/06/15

[GHS Label Elements] Symbol





### Signal Word Danger

**Hazard Statements** 

H227 Combustible liquid

H302 Harmful if swallowed

H319 Cause serious eye irritation

H351 Suspected of causing cancer

H371 May cause damage to central nervous system

H372 Causes damage to lungs through prolonged or repeated exposure.

H402 Harmful to aquatic life

# **Precautionary Statements**

[Prevention]

P201 Obtain SDS (Safety Data Sheet) and printer's operation manual before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces.-No smoking.

P260 Do not breathe vapor or mist.

P264 Wash hands thoroughly after handling.

P270 Do not eat, drink, or smoke when using this product.

P273 Avoid release to the environment.

P280 Wear protective gloves/clothing and eye/face protection.

[Response]

P301+P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P311 IF exposed or concerned: Call a POISON CENTER or doctor/physician.

P314 Get medical advice/attention if you feel unwell.

P330 Rinse mouth.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use appropriate media for extinction.

Storage

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

[Disposal]

P501 Dispose of contents and container in accordance with local, regional, national and international regulation.



> First issue: 2007/07/31 Revised: 2015/06/15

NFPA Rating (scale 0-4)

Health = 2

Flammability = 2

Instability = 0

Special = None



CANADIAN WHMIS SYMBOLS: B3, D2A, D2B





# 3. Composition / Information on Ingredients

| No | Chemical Name          | Wt%   | CAS No.      |
|----|------------------------|-------|--------------|
| 1  | Glycol ether solvents  | 75-85 | Trade Secret |
| 2  | Lactone solvent series | 10-20 | Trade Secret |
| 3  | Carbon black           | 1-5   | 1333-86-4    |
| 4  | Vinyl resin            | 1-5   | Trade Secret |
| 5  | Rust preventive        | 0.1-1 | Trade Secret |

#### 4. First Aid Measures

Inhalation : Remove person to fresh air and keep comfortable for breathing. Call

a POISON CENTER or doctor/physician.

Eye Contact : Flush eyes with plenty of water for at least 15 minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. Get

immediate medical attention.

Skin Contact : Wash with plenty of soap and water. Take off contaminated clothing

and wash before re-use. Get medical attention if irritation develops.

Ingestion : If swallowed, get medical attention.



Product Name: SS21 ink Black SDS No. 037-S080496

> First issue: 2007/07/31 Revised: 2015/06/15

Most Important Symptoms/Effects

Acute : eye irritation, central nervous system damage

Delayed : cancer, lung damage

Indication of Immediate : Tro

: Treat symptomatically and supportively.

Medical Attention and Special Treatment Needed, If Needed

# 5. Fire Fighting Measures

Flammable Properties : Flash point 71.1°C (TCC)

Auto Ignition Temperature: 169°C Flammable point: 2.2% to 33.0%

Extinguishing Media : carbon dioxide, regular dry chemical, water spray, alcohol resistant

foam

Unsuitable Extinguishing : Do not scatter spilled material with high-pressure water streams.

Media

Special Hazards Arising :

from the Chemical

**Hazardous Combustion** 

Products

Fire Fighting

Measures

: Combustible liquid and vapor.

: oxides of carbon, acid halides

: Move container from fire area if it can be done without risk. Do not scatter spilled material with high-pressure water streams. Cool containers with water spray until well after the fire is out. Stay away from the ends of tanks. Avoid inhalation of material or combustion by-products. For fires in cargo or storage area: Cool containers with water from unmanned hose holder or monitor nozzles until well after fire is out. If this is impossible then take the following precautions: Keep unnecessary people away, isolate hazard area and deny entry. Let the fire burn. Withdraw immediately in case of rising sound from venting safety device or

any discoloration of tanks due to fire.



Product Name: SS21 ink Black SDS No. 037-S080496

First issue: 2007/07/31 Revised: 2015/06/15

Special Protective

Equipment and

Precautions for

Firefighters

: Wear full protective fire fighting gear including self contained

breathing apparatus (SCBA) for protection against possible

exposure.

#### **Accidental Release Measures**

Personal Precautions,

Protective Equipment

and Emergency

Procedures

Methods and Materials

for Containment and

Cleaning Up

: Wear personal protective clothing and equipment, see Section 8.

Avoid release to the environment.

Eliminate all ignition sources if safe to do so. Stop leak if possible

without personal risk. Reduce vapors with water spray.

**Small spills:** Absorb with sand or other non-combustible material.

Collect spilled material in appropriate container for disposal.

Large spills: Dike for later disposal. Keep unnecessary people away,

isolate hazard area and deny entry. Stay upwind and keep out of low

areas.

#### Handling and Storage

Precautions for Safe

Handling

: Obtain special instructions before use. Do not handle until all safety

precautions have been read and understood. Keep away from heat,

sparks, open flame, and hot surfaces - No smoking. Do not breathe vapor or mist. Avoid contact with eyes, skin and clothing. Do not eat,

drink, or smoke when using this product. Wear protective gloves and

eye/face protection. Wash thoroughly after handling. Avoid release to

the environment.

Conditions for Safe

Storage, including any Incompatibilities

: Store and handle in accordance with all current regulations and standards. Store in a well-ventilated place. Keep container tightly

closed. Keep cool. Grounding and bonding required. Store locked up.

Keep separated from incompatible substances.



Product Name: SS21 ink Black SDS No. 037-S080496

> First issue: 2007/07/31 Revised: 2015/06/15

# 8. Exposure Controls / Personal Protection

# **Exposure Limit Values**

| No | Chemical Name               |        | TWA   |
|----|-----------------------------|--------|---|
|    |                             | ACGIH  | 3 mg/m3 TWA (inhalable fraction)  |
|    |                             | OSHA   | 3.5 mg/m3 TWA   |
| 3  | Carbon black<br>(1333-86-4) | NIOSH  | 3.5 mg/m3 TWA; 0.1 mg/m3 TWA (Carbon black in presence of Polycyclic aromatic hydrocarbons, as PAH) |
|    |                             | Mexico | 3.5 mg/m3 TWA LMPE-PPT<br>7 mg/m3 STEL [LMPE-CT]  |

Component Biological

Limit Values

: There are no biological limit values for the component(s) of this product.

# **Exposure Controls**

Occupational Exposure Controls

Appropriate
Engineering Controls

: Ventilation equipment should be explosion-resistant if explosive concentrations of material are present. Provide local exhaust or process enclosure ventilation system. Ensure compliance with applicable exposure limits.

#### Personal Protection

Respiratory

Protection

: Consult with a health and safety professional for specific respirators appropriate for your use.



**Hand Protection** 

: Wear appropriate chemical resistant gloves.



Eye Protection



: Wear splash resistant safety goggles with a faceshield. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.



First issue: 2007/07/31 Revised: 2015/06/15

# Safety Data Sheets

Skin Protection : Wear appropriate chemical resistant clothing.



### 9. Physical and Chemical Properties

Appearance - Physical State : Liquid

- Color : Black

Odor : slight solvent odor

pH : Not available

Boiling Point / Boiling Range :>=176 ℃

Melting Point / Melting Range : Not available

Decomposition Temperature : Not available

Flash Point :  $71.1^{\circ}$ C
Auto ignition temperature :  $169^{\circ}$ C

Flammability (Solid, Gas) : Not applicable
Explosive Properties : Not available
Oxidizing Properties : Not available
Upper / Lower Flammability or : 2.2% to 33.0%

**Explosive Limits** 

Vapor Pressure : Less than 133Pa(20°C)

: 0.975 (20 °C) Specific Gravity Solubility : Not available Water Solubility : Not available Partition Coefficient (n-octanol / Water) : Not available  $: 3.6 \pm 0.3(20^{\circ} \text{ C})$ Viscosity : Not available Vapor Density : Not available **Evaporation Rate** VOC : 911.2 g/L

### 10. Stability and Reactivity

Reactivity : No reactivity hazard is expected.

Chemical Stability : Stable under normal conditions of use.



Product Name: SS21 ink Black SDS No. 037-S080496

First issue: 2007/07/31 Revised: 2015/06/15

Possibility of Hazardous : Will not polymerize.

Reactions

Conditions to Avoid : Avoid flames, sparks, and other sources of ignition. Containers may

rupture or explode if exposed to heat. Avoid contact with incompatible

materials.

Incompatible Materials : acids, bases, oxidizing materials, halogens

Hazardous : Combustion: oxides of carbon, acid halides

Decomposition

#### 11. Toxicological Information

Acute Toxicity : The component(s) of this material have been reviewed in various

Component Analysis - sources and the following selected endpoints are published:

LD50/LC50

Lactone solvent series (Proprietary)

Inhalation LC50 Rat >5100 mg/m3 4 h; Oral LD50 Rat 1540 mg/kg

Information on Likely Routes of Exposure

Inhalation : irritation, nausea, headache, drowsiness, dizziness, loss of

coordination, unconsciousness, coma, lack of sense of smell, chest pain,

difficulty breathing, hearing loss, lung damage, cancer

Ingestion : irritation, nausea, headache, drowsiness, dizziness, loss of

coordination, unconsciousness, coma

Skin Contact : irritation, nausea, headache, drowsiness, dizziness, unconsciousness,

coma, skin disorders

Eye Contact : irritation

Immediate Effects : eye irritation, central nervous system damage

Delayed Effects : cancer, lung damage Medical Conditions : respiratory disorders

Aggravated by Exposure

Irritation/Corrosivity : eye irritation

Data

Respiratory : No information available for the product.

Sensitization

Dermal Sensitization : No information available for the product.

Germ Cell Mutagenicity : No information available for the product.



Product Name: SS21 ink Black SDS No. 037-S080496

> First issue: 2007/07/31 Revised: 2015/06/15

Carcinogenicity : Component Carcinogenicity

Lactone solvent series (Proprietary)

| IARC: | Monograph 71 [1999]; Supplement 7 [1987];        |
|-------|--|
| IANC. | Monograph 11 [1976] (Group 3 (not classifiable)) |

Carbon black (1333-86-4)

| ACGIH:  | A3 - Confirmed Animal Carcinogen with Unknown   |
|---------|---|
| ACGIII. | Relevance to Humans                             |
| IADO    | Monograph 93 [2010]; Monograph 65 [1996] (Group |
| IARC:   | 2B (possibly carcinogenic to humans))           |
| DFG:    | Category 3B (could be carcinogenic for man,     |
| Dr.G.   | inhalable fraction)                             |
| OSHA:   | Present   |

Vinyl resin (Proprietary)

| IARC: | Supplement 7 [1987]; Monograph 19 [1979] (Group 3 |
|-------|---|
| IARC. | (not classifiable))                               |

Reproductive Toxicity

: No information available for the product.

Specific Target Organ

: central nervous system

Toxicity - Single

Exposure

Specific Target Organ

Toxicity - Repeated

Exposure

Aspiration Hazard : No information available for the product.

### 12. Ecological Information

Handling is noted because it might influence the environment when  $% \left\{ 1,2,...,n\right\}$ 

leaking and abandoning it.

Especially, note that the product doesn't flow directly to ground, the

river, and the drain ditch.

Ecotoxicity : Harmful to aquatic life.

Component Analysis - : Lactone solvent series (Proprietary)

: lungs

**Aquatic Toxicity** 

| Almaat        | Hr EC50 Desmodesmus subspicatus: 360 mg/L;  |  |  |  |
|---------------|---|--|--|--|
| Algae:        | 96 Hr EC50 Desmodesmus subspicatus: 79 mg/L |  |  |  |
| Invertebrate: | 48 Hr EC50 Daphnia magna Straus: >500 mg/L  |  |  |  |



Product Name: SS21 ink Black SDS No. 037-S080496

> First issue: 2007/07/31 Revised: 2015/06/15

Persistence and : Not available

Degradability

Bioaccumulation : Not available
Mobility : Not available
Other Toxicity : Not available

# 13. Disposal Considerations

: Comply with all USA, national and local regulations.

Do not dump this product into sewers, on the ground or into any body

of water.

Disposal Methods : Dispose in accordance with all applicable regulations.

Component Waste : The U.S. EPA has not published waste numbers for this product's

Numbers components.

Disposal of : Empty containers may contain product residue. Dispose in

Contaminated accordance with all applicable regulations.

Packaging

# 14. Transport Information

Check a thing without a leak in a container.

Perform prevention of collapse of cargo surely.

IATA Information
 Not regulated as dangerous goods for transport.
 ICAO Information
 Not regulated as dangerous goods for transport.
 IMDG Information
 Not regulated as dangerous goods for transport.

Marine Pollutant : Lactone solvent series (Proprietary)

IBC Code: Category Y

TDG Information : Not regulated as dangerous goods for transport.

US DOT Information : Not regulated as dangerous goods for transport. \*1

\*1 Class combustible liquid (NA1993), Packing group III for quantities of 450 liters (119 gallons) or more; not regulated for smaller quantities



First issue: 2007/07/31 Revised: 2015/06/15

# 15. Regulatory Information

U.S. Federal : None of this products components are listed under SARA Sections
Regulations 302/304 (40 CFR 355 Appendix A), SARA Section 311/312 (40 CFR

370.21), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4),

TSCA 12(b), or require an OSHA process safety plan.

SARA Title III : Acute Health: Yes Section 311/312 : Chronic Health: Yes

Fire: Yes

Pressure: No Reactive: No

U.S. State Regulations : The following components appear on one or more of the following state

hazardous substances lists:

| Component    | CAS No.   | CA  | MA  | MN  | NJ  | PA  |
|--------------|-----------|-----|-----|-----|-----|-----|
| Carbon black | 1333-86-4 | Yes | Yes | Yes | Yes | Yes |

The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

WARNING! This product contains a chemical known to the state of California to cause cancer.

Canada : WHMIS CLASSIFICATION: B3, D2A, D2B.

Canadian WHMIS : Components of this material have been checked against the Canadian

Ingredient Disclosure WHMIS Ingredients Disclosure List. The List is composed of

List (IDL) chemicals which must be identified on MSDSs if they are included in products which fall under WHMIS criteria specified in the Controlled

Products Regulations and present above the threshold limits listed on

the IDL.

Carbon black (1333-86-4): 1%

Chemical Inventory : Component Analysis - Inventory

Listings

| Component                              | US  | CA  | EU  | AU  | PHIL | JP  | KR  | CN  | NZ  |
|--|-----|-----|-----|-----|------|-----|-----|-----|-----|
| Glycol ether solvents<br>(Proprietary) | Yes | NSL | EIN | No  | No   | Yes | No  | Yes | No  |
| Lactone solvent series (Proprietary)   | Yes | DSL | EIN | Yes | Yes  | Yes | Yes | Yes | Yes |



First issue: 2007/07/31 Revised: 2015/06/15

# Safety Data Sheets

| Carbon black<br>(1333-86-4)   | Yes | DSL | EIN | Yes | Yes | Yes | Yes | Yes | Yes |
|-------------------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| Vinyl resin<br>(Proprietary)  | Yes | DSL | No  | Yes | Yes | Yes | Yes | Yes | Yes |
| Rust preventive (Proprietary) | Yes | DSL | EIN | Yes | Yes | Yes | No  | Yes | Yes |

#### 16. Other Information

### Key/Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; CAS - Chemical Abstracts Service; CLP - Classification, Labelling and Packaging; EEC - European Economic Community; EIN (EINECS) - European Inventory of Existing Commercial Chemical Substances; ELN (ELINCS) - European List of Notified Chemical Substances; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IMDG - International Maritime Dangerous Goods; IBC Code - International Bulk Chemical Code; Kow - Octanol/water partition coefficient; LEL - Lower Explosive Limit; LOLI - List Of LIsts<sup>TM</sup> - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NTP = National Toxicology Program; REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - European Rail Transport; STEL - Short-term Exposure Limit; TWA - Time Weighted Average; UEL - Upper Explosive Limit

#### Other Information

This information is furnished without warranty, express or implied, except that it is accurate to the best knowledge of Mimaki Engineering Corporation.

It relates only to the specific material designated herein, and does not relate to use in combination with any other material or process.

Mimaki Engineering Corporation assumes no legal responsibility for use or reliance upon this information.