

GANS INK & SUPPLY CO.

www.gansink.com

TECHNICAL BULLETIN # 224 09.05

CAMRAY PLUS 4-COLOR PROCESS INKS

Ink Number	Description	Tack
A130620	Camray Plus Process Black	14.5
A130621	Camray Plus Process Cyan	14.0
A130622	Camray Plus Process Magenta*	12.5
A130623	Camray Plus Process Yellow	10.5

*B/S magenta in keeping with the color balance of Pacific rim process sets.

A130622Y, a yellow shade magenta similar to SWOP standards is also available.

Tack readings are @ 1200 RPM, I minute 90° Fahrenheit, on a Thwing Albert 101 Inkometer.

Application

Camray Plus is a very quick setting process series with color balance similar to Pacific Rim process sets. It is equally suited to the unique inking and dampening systems of large and small format multi-unit presses. Camray Plus is faster drying and has better scuff resistance than Camray.

suitability with laser imprinting. Highly alkaline coatings such as Krystal Kote

are not advisable, but use of A130622Y alleviates these concerns.

Features & Benefits

Set speeds and surface dry times are among the fastest of Pacific Rim quick-set process inks. Camray Plus Inks are specifically formulated for work & turn/tumble and print-on-demand jobs on C1S & C2S offset stock. Camray Plus is not recommended for printing on non-porous substrates.

Stay-Open

Camray Plus will stay-open for 1-2 days depending upon ambient conditions.

Camray Plus has excellent scuff resistance when fully cured.

Camray Plus has excellent transferability from plate to blanket and substrate.

This is a finishing friendly set, but pre-testing is necessary for establishing

Condition of the control of the cont