

**1. Product and Company Identification**

Product number 066-003
Product name **66 Spray Adhesive**
Effective date 11-Feb-2011
Company information Sprayway, Inc.
484 Vista Ave.
Addison, IL 60101 United States
Company phone General Assistance 1-630-628-3000
Emergency telephone US 800-424-9300
Emergency telephone outside US 703-527-3887
Version # 07
Supersedes date 28-Jul-2010

2. Hazards Identification

Emergency overview Aerosol. EXTREMELY FLAMMABLE
CONTENTS UNDER PRESSURE. Will be easily ignited by heat, spark or flames.
Irritating to eyes. Prolonged exposure may cause chronic effects.

Potential health effects

Routes of exposure Skin contact. Ingestion.

Eyes Contact with eyes may cause irritation.

Skin Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

Inhalation Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Prolonged inhalation may be harmful.

Ingestion Exposure by ingestion of an aerosol is unlikely. May cause delayed lung damage. Components of the product may be absorbed into the body by ingestion.

Target organs Central nervous system. Lungs.

Chronic effects May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion, and blurred vision) and/or damage. May cause delayed lung damage. Prolonged skin contact may defat the skin and produce dermatitis.

Signs and symptoms Discomfort in the chest. Narcosis. Defatting of the skin. Irritation.

3. Composition / Information on Ingredients

Components	CAS #	Percent
Cyclohexane	110-82-7	30 - 40
n-Butane	106-97-8	15 - 20
Dimethyl Ether	115-10-6	10 - 15
Propane	74-98-6	10 - 15
Isobutane	75-28-5	8 - 10
Non-hazardous and other components below reportable levels		10 - 20

4. First Aid Measures**First aid procedures**

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops or persists.

Skin contact Immediately take off all contaminated clothing. Wash off with warm water and soap. Get medical attention if irritation develops or persists.

Inhalation Move to fresh air. If symptoms persist, get medical attention.

Ingestion

If material is ingested, immediately contact a poison control center. Have victim rinse mouth thoroughly with water. Do not induce vomiting without advice from poison control center. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Notes to physician

Symptoms may be delayed.

5. Fire Fighting Measures**Flammable properties**

Vapor or gas may spread to distant ignition sources and flash back. Runoff to sewer may cause fire or explosion hazard.

Extinguishing media**Suitable extinguishing media**

Foam. Dry chemical. Carbon dioxide (CO₂). Do not use water jet. Water may be ineffective.

Protection of firefighters**Specific hazards arising from the chemical**

Fire may produce irritating, corrosive and/or toxic gases.

Protective equipment and precautions for firefighters

In the event of fire and/or explosion do not breathe fumes. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Containers should be cooled with water to prevent vapor pressure build up. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

6. Accidental Release Measures**Methods for containment**

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Stop the flow of material, if this is without risk. Prevent entry into waterways, sewers, basements or confined areas.

Methods for cleaning up

Should not be released into the environment. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean contaminated surface thoroughly.

7. Handling and Storage**Handling**

Pressurized container: Do not pierce or burn, even after use. Do not handle or store near an open flame, heat or other sources of ignition. Do not smoke while using or until sprayed surface is thoroughly dry. Do not use if spray button is missing or defective. Use only with adequate ventilation. Do not get this material in contact with eyes. Do not get this material in contact with skin. Wear personal protective equipment. Avoid prolonged exposure.

Storage

Level 3 Aerosol.

Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Do not handle or store near an open flame, heat or other sources of ignition. Avoid exposure to long periods of sunlight. Store in cool place. Keep in an area equipped with sprinklers. Keep out of the reach of children. Level 3 Aerosol. Do not store, incinerate, or heat this material above 120 degrees Fahrenheit.

8. Exposure Controls / Personal Protection**Exposure limits****ACGIH****Components****CAS #****TWA****STEL****Ceiling**

Cyclohexane

110-82-7

100 ppm

Not established

Not established

n-Butane

106-97-8

1000 ppm

Not established

Not established

Propane

74-98-6

1000 ppm

Not established

Not established

Isobutane

75-28-5

1000 ppm

Not established

Not established

OSHA**Components****CAS #****TWA****STEL****Ceiling**

Cyclohexane

110-82-7

300 ppm

Not established

Not established

Propane

74-98-6

1000 ppm

Not established

Not established

Personal protective equipment**Eye / face protection**

Wear chemical goggles.

Skin protection

Wear appropriate chemical resistant clothing. Protective gloves.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

9. Physical & Chemical Properties

Appearance	Compressed liquefied gas.
Boiling point	64.4 °F (17.8 °C) estimated
Color	Tan.
Density	0.6689 g/cm3 estimated
Flammability (HOC)	42.4775 kJ/g estimated
Flash back	Yes
Flash point	-156 °F (-104.4 °C) Propellant
Form	Liquid. Aerosol.
Freezing point	Not available
Odor	Solvent.
pH	Not applicable
Physical state	Liquid.
Pressure	55 - 75 psig @ 70F
Solubility	None
Specific gravity	0.669

10. Chemical Stability & Reactivity Information

Chemical stability	Risk of ignition.
Conditions to avoid	Heat, flames and sparks.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological Information

Acute effects	Acute LD50: 5244 mg/kg estimated, Rat, Dermal	
Component analysis - LD50		
Toxicology Data - Selected LD50s and LC50s		
Cyclohexane	110-82-7	Inhalation LC50 Rat 13.9 mg/L 4 h; Oral LD50 Rat >5000 mg/kg; Dermal LD50 Rabbit >2000 mg/kg
Dimethyl Ether	115-10-6	Inhalation LC50 Rat 308.5 mg/L 4 h
Isobutane	75-28-5	Inhalation LC50 Rat 658 mg/L 4 h
n-Butane	106-97-8	Inhalation LC50 Rat 658 mg/L 4 h
Propane	74-98-6	Inhalation LC50 Rat 658 mg/L 4 h
Sensitization	Not expected to be hazardous by OSHA criteria.	
Teratogenicity	Not expected to be hazardous by OSHA criteria.	

12. Ecological Information

Ecotoxicity	Components of this product are hazardous to aquatic life.
	LC50 11.98 mg/L, Fish, 96.00 Hours, IC50 1322 mg/L, Algae, 72.00 Hours,

13. Disposal Considerations

Waste codes	D001: Waste Flammable material with a flash point <140 F
--------------------	--

Disposal instructions

Contents under pressure. Do not puncture, incinerate or crush. Dispose of this material and its container at hazardous or special waste collection point. Do not allow this material to drain into sewers/water supplies. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose in accordance with all applicable regulations.

14. Transport Information**Department of Transportation (DOT) Requirements****Basic shipping requirements:**

Proper shipping name	Consumer commodity
Hazard class	ORM-D
Subsidiary hazard class	None
Additional information:	
Packaging exceptions	156, 306
Packaging non bulk	156, 306
Packaging bulk	None

IMDG**Basic shipping requirements:**

Proper shipping name	AEROSOLS
Hazard class	2.1
UN number	1950
Additional information:	
Packaging exceptions	LTD QTY
Item	5F
Labels required	None
Transport Category	2

**IATA****Basic shipping requirements:**

Proper shipping name	Aerosols, flammable
Hazard class	2.1
UN number	1950
Additional information:	
Packaging exceptions	LTD QTY
Labels required	2.1

**15. Regulatory Information****US federal regulations**

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

U.S. - CERCLA/SARA - Section 313 - Emission Reporting

Cyclohexane 110-82-7 1.0 % de minimis concentration

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous chemical Yes

CERCLA (Superfund) reportable quantity

Cyclohexane: 1000.0000

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 302 extremely hazardous substance	No
Section 311 hazardous chemical	Yes
Hazard categories (311/312)	Immediate Hazard - Yes Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of New and Existing Chemicals (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations**U.S. - Pennsylvania - RTK (Right to Know) List**

Cyclohexane	110-82-7	Environmental hazard
Dimethyl Ether	115-10-6	Present
Isobutane	75-28-5	Present
n-Butane	106-97-8	Present
Propane	74-98-6	Present

16. Other Information**Further information**

HMIS® is a registered trade and service mark of the NPCA.

HMIS® ratings

Health: 1*
Flammability: 4
Physical hazard: 0

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

MSDS sections updated

Product and Company Identification: Product and Company Identification

Prepared by

Regulatory Compliance