

Safety Data Sheet

In compliance with OSHA Hazard Communication Standard (29 CFR 1910.1200)

SECTION 1: IDENTIFICATION

SDS Number: 506, version 12/9/2016

(a) Product identifier

Gans Item ID: UV56-7500, UV62-7500, UV76-7500, UV76-7501, UV76-7502, UV38-7500, UV43-7500, UV49-7500, UV00-7500, UV99-7500, UV00-7501, UV38-7501, UV58-7500, UVNG001, UVNG002, UVNG003, UVNG004, UVNG006, UVNG007, UVNG008, UVNG009, UVNG010, UVNG011, UVNG013; **New-Gen XLT Pantone Reference Color: Where # is any whole**

number from 0 to 9: UVNG###, UVNG####

UV15758, UV15759, UV15760, UV15761, UV15806, UV15862, UV15863, UV16050, UV16101, UV16170

Gans Description: New-Gen XLT Mixing, New-Gen XLT Proc (Process), UV Pearl Spec Beige Wynn, UV Pearl O.P.V., New-Gen XLT MICR Black

(b) Other means of identification

General description: UV-curing, lithographic printing ink

(c) Recommended use

Product Use: Industrial use only; printing ink for use on lithographic printing press equipped with UV curing lamps.

Restrictions on use: Not for residential use.

(d) Supplier's details

Manufacturer: Gans Ink and Supply Co, Inc.

Address: 1441 Boyd Street

Los Angeles, CA 90033

Contact Person: Marco Ramos
Telephone: 323- 264-2200 x139
Email: MSDS@gansink.com

(e) Emergency telephone number:

Available only during business hours.

(323) 264-2200 Monday- Friday 7:00 A.M. – 9:00 P.M.

24 Hours Response: Los Angeles County Fire Department / HazMat. Department

SECTION 2: HAZARD(S) IDENTIFICATION

(a) Classification

- This mixture is hazardous according to OSHA Hazard Communication Standard (29 CFR 1910.1200).
- Physical hazards: Not classified as hazardous
- Health hazards:
 - Eye Damage -- Category 1



Skin Sensitization - Category 1A

- o Reproductive Toxicity Category 2
- Aquatic Toxicity, Acute Category 2
- o Aquatic Toxicity, Chronic Category 2

(b) Label elements

Signal Word: Danger

Hazard Statements: Causes serious eye damage. May cause an allergic skin reaction. May damage fertility or the unborn child. Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Precautionary Statements:

Prevention: Wear eye protection/face protection. Avoid breathing mist/vapors/spray. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Avoid release to the environment.

Response:

If exposed or concerned: Get medical advice/attention.

If swallowed: If exposed or concerned: Get medical advice/attention.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Collect spillage. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard Pictograms:



(c) Hazards not otherwise classified

None known

(d) Ingredients of unknown acute toxicity

NA

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture: Mixture

TS = Trade Secret (as specified by substance manufacturer)

Substance	CAS # (TS= Trade Secret)	Min. conc.	Max. conc.
Epoxy acrylate oligomer	55818-57-0	0.0%	21.5%
Blue pigment: 2-[(4-{(4-anilinophenyl)[4-(phenylimino)cyclohexa-2,5-	1324-76-1	0.0%	20.0%
dien-1-ylidene]methyl}phenyl)amino]benzenesulfonic acid			
2-Propenoic acid, reaction products with pentaerythritol	1245638-61-2	0.0%	12.0%



	CAG II (IDG ID I G A)	3.5	3.6
Substance	CAS # (TS= Trade Secret)	Min. conc.	Max. conc.
Monomer	TS	0.0%	11.2%
Urethane acrylate oligomer	TS	0.0%	11.1%
Polyester Acrylate	TS	0.0%	10.8%
DiTrimethylolpropane Tetraacrylate	94108-97-1	0.0%	10.8%
Trimethylolpropanetriacrylate	15625-89-5	0.0%	9.0%
Glycerol propoxylate triacrylate	TS	0.0%	6.0%
Esterfification product of poly[oxy(methyl-1,2-ethanediyl)],	84170-74-1	0.0%	6.0%
.alpha.,.alpha.'-(2,2-dimethyl-1,3-propanediyl)bis[.omegahydroxy- and			
prop-2-enoic acid			
Polyester Acrylate	TS	0.0%	5.6%
Gans UVP-2002	TS	0.0%	4.8%
Pentaerythritol triacrylate	3524-68-3	0.0%	4.3%
Pentaerythritol tetraacrylate	4986-89-4	0.0%	4.3%
Acrylated resin	TS	0.0%	3.1%
2,6-di-tert-butyl-p-cresol	128-37-0	0.0%	3.0%
Gans UVP-2035	TS	0.0%	3.0%
Rosin	8050-09-7	0.0%	2.7%
Gans UVP-2044	TS	0.0%	2.0%
2-Ethylhexanoic Acid	149-57-5	0.0%	0.8%
Glycerol, propoxylated, esters with acrylic acid	52408-84-1	0.0%	0.6%
Gans UVP-2008	TS	0.0%	0.5%
Epoxy Acrylate Oligomer	TS	0.0%	0.4%
Triphenylphosphine	603-35-0	0.0%	0.1%
Tris(N-hydroxy-N-nitrosophenylaminato-O,O')aluminium	15305-07-4	0.0%	0.1%

SECTION 4: FIRST AID MEASURES

(a) Description of first aid measures:

Ingestion: If exposed or concerned: Get medical advice/attention.

Eye contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Skin contact: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Inhalation: No recommendation

(b) Most important symptoms and effects, both acute and delayed:

Ingestion: Harmful if swallowed. May damage fertility or the unborn child.

Eye contact: Causes serious eye damage.

Skin contact: May cause an allergic skin reaction

(c) Indication of any immediate medical attention and special treatment needed:

Symptoms such as burning or pain to eyes or skin may indicate exposure and the need for first aid.

SECTION 5: FIRE – FIGHTING MEASURES

(a) Extinguishing Media:

Suitable extinguishing media: Use CO₂, dry chemical, fire-fighting foam, or water fog extinguishing media **Unsuitable extinguishing media:** Do not use water stream. Water stream or spray is OK to cool containers only.



(b) Special hazards arising from the substance or mixture: Thermal decomposition or combustion products may include COx, and NOx. High pressure my build up in heated containers.

(c) Special protective equipment and precautions for fire-fighters: Wear NIOSH approved self-contained respiratory protective device, and fully protective fire-fighting suit.

SECTION 6: ACCIDENTAL RELEASE MEASURES

(a.i) Personal precautions:

No smoking or other sources of ignition near spillage.

Avoid direct contact with spilled material.

Wear all Personal Protection listed in Section 8 before directly contacting spilled material

Ensure there is adequate area ventilation, and avoid excessive inhalation of fumes.

(a.ii) Protective equipment: See Section 8

(a.iii) Emergency procedures: If dangerous conditions exist, contact emergency response personnel, follow emergency procedures, and contact emergency response authorities.

(b) Methods for containment and cleaning up:

If it is safe to do so, adjust leaking containers to reduce or eliminate the continued release. Wear all Personal Protection listed in Section 8 before directly contacting spilled material. For high viscosity materials, scoop or shovel material into appropriate container for reuse, recycling, or disposal. For low viscosity materials, first surround and then cover spilled material with inert absorbent (vermiculite, or similar). Then scoop or shovel material into appropriate container for reuse, recycling, or disposal.

Residual material can be cleaned with UV blanket wash, acetone, or other press solvent.

Consult your company's spill procedure for details of regulatory restrictions and recommendations.

Do not allow spilled materials, or clean up materials to enter storm drains or natural water ways.

SECTION 7: HANDLING AND STORAGE

(a) Precautions for safe handling:

Wear eye protection/face protection.

Avoid breathing mist/vapors/spray.

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

Wear protective gloves/protective clothing/eye protection/face protection.

Contaminated work clothing must not be allowed out of the workplace.

Avoid release to the environment.

(b) Conditions for safe storage:

Store locked up.

Store in original container and keep containers covered and sealed.

Store in cool, dry, well-ventilated place.

Appropriate storage temperature is approximately 7° - 35° C (45° - 95° F).

Incompatibilities: Avoid contact with heat, sources of ignition, sunlight, and strong oxidizers.



SECTION 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

(a) Permissible exposure limits		OSHA PEL		Cal/OSHA	NIOSH	ACGIH
			PEL	REL	2015 TVL	
Substance	CAS#	ppm	mg/m ³	8-hour	Up to 10-	8-hour
				TWA (ST)	hour	TWA (ST)
				STEL (C)	TWA	STEL (C)
				Ceiling	(ST)	Ceiling
					STEL (C)	
					Ceiling	
No hazardous ingredients						
appear on OSHA Annotated						
Tables Z-1, Z-2, or Z-3.						

(b) Appropriate engineering controls:

Ventilation requirements: Adequate ventilation in accordance with good engineering practice must be provided. **General protective measures:** Ensure that eye flushing /eye wash stations, and hand washing areas are accessible.

(c) Personal protective equipment:

Inhalation: Avoid breathing mist/ vapors/spray. Where mist or aerosol is present, an organic vapor respirator is recommended.

Skin Contact: Wear protective gloves/protective clothing. Contaminated work clothing must not be allowed out of the workplace. Neoprene or nitrile gloves are recommended. PVC gloves are not compatible. Always wear long sleeves and where exposure potential is high, a neoprene or other chemical resistant apron is recommended.

Eye Contact: Wear eye protection/face protection. Eye and face protective devices must comply with ANSI Z87.1-1989. Recommended eye protection: goggles, flexible fitting, hooded ventilation. A transparent face shield is recommended.

Ingestion: Avoid eating, drinking, or smoking in work area and wash hands after handling this product.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

(a) Appearance (physical state, color): Viscous paste or liquid, various colors

(b) Odor: Ester-like

(c) Odor threshold: Data not available

(d) pH: Data not available

(e) Melting point/ freezing point; Data not available(f) Initial Boiling point / Range: Data not available

(g) Flashpoint: > 212 °F (> 100 °C)
(h) Evaporation Rate: Data not available

(i) Flammability (solid/gas): Not classified as flammable/ Not classified as flammable

(j) Upper/lower flammability explosion limits: Data not available

(k) Vapor Pressure (mm Hg @ 68°F): Data not available

(l) **Vapor Density** (Air = 1): Data not available (m) **Relative Density** ($H_2O = 1$): 1.2 approximate

(n) Solubility: insoluble in water

(o) Partition coefficient n- Octanol/ Water: Data not available

(p) Auto-ignition temperature: Data not available(q) Decomposition temperature: Data not available

(r) Viscosity: Data not available



Other properties

VOC % (wt): ≤ 1.0 **VOC** (lbs./gal): ≤ 0.11

SECTION 10: STABILITY AND REACTIVITY INFORMATION

- a) **Reactivity:** Not reactive under normal storage conditions. See Section 7. Mixture will undergo polymerization reaction in the presence of sunlight, bright industrial lights, or high temperatures.
- **(b) Chemical stability:** Mixture is chemically stable under normal storage and handling conditions, and under normal temperatures and pressures.
- (c) Possibility of hazardous reactions: Exposure to excess heat may cause exothermic polymerization reaction.
- (d) Conditions to avoid: Avoid contact with heat (temperature > 100° F, 38° C), sources of ignition, sunlight, and strong oxidizers.
- (e) Incompatible materials: Radical forming initiators, peroxides or other strong oxidizers, strong alkalis or reactive metals.
- (f) Hazardous decomposition product: No data available.

SECTION 11: TOXICOLOGICAL INFORMATION

(a) Likely routes of exposure: Skin contact, eye contact, inhalation, ingestion

(b) Symptoms related to physical, chemical, and toxicological characteristics:

Skin contact: There may be irritation and redness at site of contact.

Eye contact: There may be irritation and redness. Eyes may water profusely.

Inhalation: No data available

Ingestion: There may be irritation and redness of the mouth and throat, and a feeling of illness.

(c) Delayed and immediate effects, and chronic effects from long-term exposure

No data available

(d) Numerical measures of toxicity:

	CAS # (TS=			
Substance	Trade Secret)	Dermal	Oral	Inhalation
Epoxy acrylate oligomer	55818-57-0	LD50 2000 mg/kg	LD50 2000 mg/kg	Data not available
		bw (rat)	bw (rat)	Data not available
Blue pigment: 2-[(4-{(4-anilinophenyl)[4-(phenylimino)cyclohexa-2,5-dien-1-ylidene]methyl}phenyl)amino]benzenesulfonic acid	1324-76-1	LD50 2000 mg/kg bw (rabbit)	LD50 5000 mg/kg bw (rat)	Data not available
2-Propenoic acid, reaction products with pentaerythritol	1245638-61-2	Discriminating dose 2000 mg/kg bw (rabbit)	LD50 420 - 620 mg/kg bw (rat)	Data not available
Monomer	TS	Data not available	Data not available	Data not available
Urethane acrylate oligomer	TS	Data not available	Data not available	Data not available
Polyester Acrylate	TS	Data not available	Data not available	Data not available
DiTrimethylolpropane Tetraacrylate	94108-97-1	Data not available	LD50 5000 mg/kg bw (rat)	Data not available
Trimethylolpropanetriacrylate	15625-89-5	LD50 4.7 mL/kg	LD50 5000 mg/kg	LC50 (6 h) 550
		bw (rabbit)	bw (rat	mg/m³ air (rat)
Glycerol propoxylate triacrylate	TS	Data not available	Data not available	Data not available
Esterfification product of poly[oxy(methyl-	84170-74-1			
1,2-ethanediyl)], .alpha.,.alpha.'-(2,2-dimethyl-		LD50 2000 mg/kg	LD50 5000 mg/kg	LC50 (4 h) 2 mg/L
1,3-propanediyl)bis[.omegahydroxy- and prop-2-enoic acid		bw (rat)	bw (rat)	air (rat)



	CAS # (TS=		T	
Substance	Trade Secret)	Dermal	Oral	Inhalation
Polyester Acrylate	TS	Data not available	Data not available	Data not available
Gans UVP-2002	TS	LD50 1340 - 2756 mg/kg bw (rat)	Data not available	LD50 2000 mg/kg bw (rat)
Pentaerythritol triacrylate	3524-68-3	Data not available	Data not available	Data not available
Pentaerythritol tetraacrylate	4986-89-4	Data not available	Data not available	Data not available
Acrylated resin	TS	Data not available	Data not available	Data not available
2,6-di-tert-butyl-p-cresol	128-37-0	LD50 2000 mg/kg bw (rat)	LD50 2930 - 6000 mg/kg bw (rat)	Data not available
Gans UVP-2035	TS	LD50 2000 mg/kg bw (rat)	LD50 5000 mg/kg bw (rat)	Data not available
Rosin	8050-09-7	LD50 2000 mg/kg bw (rat)	LD50 1000 - 5000 mg/kg bw (rat)	Data not available
Gans UVP-2044	TS	Data not available	Data not available	Data not available
2-Ethylhexanoic Acid	149-57-5	LD50 2000 mg/kg bw (rat	LD50 2043 mg/kg bw (rat)	LC0 (8 h) 110 mg/m³ air (rat)
Glycerol, propoxylated, esters with acrylic acid	52408-84-1	LD50 2000 mg/kg bw (rabbit)	LD50 2000 mg/kg bw (rat)	Data not available
Gans UPV-2008	TS	LD50 2000 mg/kg bw (rat)	LD50 2000 mg/kg bw (rat)	Data not available
Epoxy Acrylate Oligomer	TS	Data not available	Data not available	Data not available
Triphenylphosphine	603-35-0	LD50 700 mg/kg	LC50 (4 h) 12.5	LD50 2500 mg/kg
		bw (rat)	mg/L air (rat)	bw (rat)
Tris(N-hydroxy-N-nitrosophenylaminato- O,O')aluminium	15305-07-4	Data not available	Data not available	Data not available

(e) Carcinogens information: No ingredients in this mixture are known to be listed by the National Toxicology Program (NTP) Report on Carcinogens, or have been found to be potential carcinogens in the International Agency for Research on Cancer (IARC), or by OSHA.

SECTION 12: ECOLOGICAL INFORMATION

(a) Ecotoxicity

Classification of mixture:

Aquatic Toxicity, Acute - Category 2

o Aquatic Toxicity, Chronic - Category 2

(b) Persistence and degradability: No data available

(c) Bioaccumulative potential: No data available.

(d) Mobility in soil: No data available

(e) Other adverse effects: No known adverse effects

SECTION 13: DISPOSAL CONSIDERATIONS

Dispose of contents/container in accordance with local/regional/national regulations.

This product does ${\bf NOT}$ exhibit the characteristics of a RCRA hazardous waste as defined under 40CFR261.

SECTION 14: TRANSPORT INFORMATION

US DOT (Ground):

(a) UN number: UN3082



(b) UN Proper Shipping Name: Environmentally hazardous substance, liquid, n.o.s.

(c) Transport hazard class: 9 (d) Packing Group: III

(e) Environmental hazards: Marine Pollutant

(f) Transport in bulk MARPOL 73/78:

IBC:

(g) Special Precautions: None known

SECTION 15: REGULATORY INFORMATION

U.S. Federal Regulations

TSCA Section 8(b) Inventory Status: All ingredients of this mixture are listed on the TSCA Inventory

EPCRA, **Section 302 – Extremely hazardous substances:** This mixture does not contain listed materials.

CERCLA Hazardous Substances: This mixture does not contain listed materials.

EPCRA Section 313 Toxic Chemicals: This mixture does not contain listed materials.

CAA 112(r) Regulated Chemicals for Accidental Release Prevention: This mixture does not contain listed materials.

Hazardous Air Pollutants (HAP): This mixture does not contain listed materials.

U.S. State Regulations

California Proposition 65: This mixture does not contain listed materials.

Canadian Environmental Protection Act: No data available.

European Chemical Agency (ECHA):

Substances of Very High Concern (SVHC): This mixture does not contain listed materials.

SECTION 16: OTHER INFORMATION

The information herein is presented in good faith, based on the data available to us and is believed to be correct as of the date hereof. However, Gans Ink and Supply Co., Inc. makes no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Gans Ink and Supply Co., Inc. assumes no responsibility for any damages of any nature directly or indirectly resulting from the use of or reliance upon the information contained herein. Users must make their own determination as to the suitability of the product for their purpose prior to use. In accordance with good practices of personal cleanliness and hygiene, handle with due care and avoid unnecessary contact with this product.

