Material Safety Data Sheet # 117.2

For Printing Inks and related Materials OSHA Hazard Communication Standard, 29 CFR 1910.1200

Date of preparation: 9/30/2010 MSDS#: 117.2

I. PRODUCT IDENTIFICATION

Manufacturer: Gans Ink and Supply Co, Inc. Address: 1441 Boyd Street Los Angeles, CA 90033	HMIS HAZARD IDENTIFICATION Health 1	
Emergency phone: (323) 264-2200	Flammability 1	
	Reactivity 1	
	Personal B	
	Protection	
Product Class: Lithographic Printing Ink	Manufacturer's code: Various including, 26919,	
	14656- 58, 11732, A111134, 24886, A106486,	
	A113684, A118677, A113777, A114967, A124662	
Trade Name: Soytech Web Forms Fluorescent Inks (P801 – 814)		

II. HAZARDOUS INGREDIENTS					
Material	CAS#	%	Exposure Limits	Units	
No Hazardous ingredients known at this time.					
OSHA HAZARD COMMUNICATION STANDARD , 29 CFR 1910.1200					
This product is not considered hazardous as defined					

III. HEALTH HAZARD INFORMATION

Effects of Overexposure

Inhalation: Avoid inhalation. Caution should be taken to prevent aerosolization or misting of this product. Acute overexposure may result in irritation of the throat and lungs. Out gassing of formaldehyde vapors may cause throat irritation.

Skin Contact: Avoid skin contact. This product may be slightly irritating to the skin upon direct contact. Prolonged or repeated contact may result in contact dermatitis which is characterized by dryness, chapping, and reddening. This condition may make the skin more susceptible to other irritants, sensitizers, and disease. Pre-existing skin conditions may make the skin more susceptible and facilitate uptake by this route.

Eve Contact: Avoid eye contact. This product may be slightly irritating to the eyes upon direct contact. Exposure to high concentrations of vapors may be irritating to the eyes.

Ingestion: Do not ingest. Ingestion of small quantities is usually nonfatal unless aspiration occurs. Severe oral intoxication will lead to intense burning of the throat and may result in drowsiness, dullness, numbness, and headache followed by dizziness, weakness, and nausea. Loss of consciousness and convulsions followed by death may result. See Notes to Physician section below.

IV. FIRST AID PROCEDURES

Emergency & First Aid Procedures

Eyes: Immediately flush eyes with large amounts of water and continue flushing for 15 minutes, while holding eyelids open until irritation subsides. If irritation persists, seek medical attention.

Skin: Remove contaminated clothing. Wash contaminated area thoroughly with soap and water. If redness or irritation occurs, seek medical attention.

Inhalation: If mist or exposure is generated when the material is heated or handled, remove victim from exposure. If breathing has stopped or is irregular, administer artificial respiration and supply oxygen if it is available. If victim is unconscious, remove to fresh air and seek medical attention.

Ingestion: Do not induce vomiting. Seek immediate medical attention.

Notes to Physician: Aspiration may lead to chemical pneumonitis which is characterized by pulmonary edema and hemorrhage, and may be fatal. Signs of lung involvement include increased respiration rate, increased heart rate, and a bluish discoloration of the skin. Coughing, choking, and gagging are often noted at the time if aspiration. Gastrointestinal discomfort may develop, followed by vomiting, with risk of aspiration.

V. FIRE AND EXPLOSION DATA

Flash Point ° F: > 300 F	Auto-ignition T	emperature °F: No Data
Flammable Limits in Air (% Volume)	Lower Limit: No Data	Upper Limit: No Data

Extinguishing Media: Use water fog, alcohol foam, CO₂, or dry chemical extinguishing media. **Special Fire Fighting Procedures:** Water can be used to cool containers exposed to heat or flame. During a fire, irritating and toxic gases may be formed. Firefighters use self contained breathing apparatus and suitable protective equipment.

Unusual Fire & Explosion Hazard: Dense smoke may be generated while burning; carbon dioxide, carbon monoxide, and other oxides may be generated as products of combustion.

VI. ACCIDENTAL RELEASE

Steps to be taken in event of spill or release: Absorb with inert material, such as vermiculite, clay, silica gel etc. Scrape up with trowel or scoop and place in a suitable container. Clean up with a suitable solvent. Do not allow to enter waterways, sewers or drains.

VII. HANDLING AND STORAGE

Handling and Storage: Store in containers in a cool, well-ventilated area. Keep away from heat, sparks, open flame and other sources of ignition. Avoid prolonged contact with skin, contact with eyes, and breathing of mist or vapor. Consumption of food and beverages should be avoided in work areas. Always wash hands and face with soap and water before eating, drinking, and smoking.

Other Precautions: For industrial use only. Do not ingest. Avoid prolonged contact with skin, contact with eyes, and breathing of mist or vapor.

VIII. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Ventilation Requirements: If vapor or mist is generated when the material is heated or handled, adequate ventilation in accordance with good engineering practice must be provided to maintain concentrations below the specific exposure or flammable limits.

Personal Protective Equipment

Respirator: Respiratory protection is not required under conditions of normal use. If vapor or mist is generated when the material is heated or handled, use an organic vapor respirator with a dust and mist filter. All respirators must be NIOSH certified. A NIOSH approved respirator with a combination formaldehyde/HEPA cartridge is recommended. Do not use compressed oxygen in hydrocarbon atmospheres.

Skin: Where contact is likely, use chemical resistant gloves, apron and boots over parts of the body subject to exposure.

Eye: If material is handled such that it could be splashed into eyes, wear plastic face shield or splash-proof safety glasses or goggles.

IX. PHYSICAL AND CHEMICAL DATA

Boiling Range ° F : 500 – 600 F	Vapor Density (Air = 1): > 1
Relative Density ($H_2O = 1$): 1.04 – 1.12	Vapor Pressure (mm Hg @ 68°F): No Data
Material Density Lbs./Gal: 8.66 - 9.33	Solubility in Water: Insoluble
% Volatile Organic Compounds (VOC) by	% Solids by Weight: 88 – 96.5
Weight: 3.5 – 12.0	
VOC: lbs/gal: 1.12 g/L: 134	Appearance/Odor: Colored paste

X. STABILITY AND REACTIVITY INFORMATION

Stability (Thermal, Light, etc.): Stable	Conditions to avoid: Excessive heat, sparks, open	
	flame and sources of ignition.	
Hazardous Polymerization: Will not occur.	Materials to avoid: Strong oxidizers.	
Hazardous Decomposition Products: CO ₂ , CO, nitrogen, sulfur and other oxides may be generated as		
products of combustion.		

XI. TOXICOLOGICAL INFORMATION

CARCINOGEN: This product has not been identified as a carcinogen by OSHA or the National

Toxicology Program (NTP), or the International Agency for Research Cancer (IARC).

Mutagen:No DataTeratogen:No DataReproductive Toxicity:No Data

No Toxicological studies have been conducted on this product.

XII. ECOLOGICAL INFORMATION

This product has not been evaluated at this time. As with all inks, do not allow to enter waterways, drains, sewers etc.

XIII. DISPOSAL INFORMATION

Waste Disposal Method: If recycling as ink is not possible, material may be incinerated or land filled at a licensed facility in accordance with local, state, and federal regulations.

XIV. TRANSPORT INFORMATION

Flammability Classification: Combustible OSHA: Class III B Not Regulated IMO/ IMDG: Not Regulated IATA/ ICAO: Not Regulated

Not classified as dangerous in the meaning of transport regulations.

XV. REGULATORY INFORMATION

SARA Title III Section 313:

This material Does Not contain chemicals subject to the reporting requirements of the SARA Superfund Amendments and Reauthorization Act.

TSCA Section 8(b) Inventory Status:

All component(s) of this product are either exempt or listed on the TSCA Inventory.

U.S. State Regulations

California Proposition 65:

This product contains a chemical known by the state of California to cause cancer

Chemical CASFormaldehyde 00050-00-0

It has been determined that under thermal decomposition, air concentrations reaching or exceeding 0.1 ppm Formaldehyde may occur.

XVI. OTHER INFORMATION

The information herein is presented in good faith, based on the data available to us and is believed to be correct as of the date hereof. However, Gans Ink and Supply Co., Inc. makes no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Gans Ink and Supply Co., Inc. assumes no responsibility for any damages of any nature directly or indirectly resulting from the use of or reliance upon the information contained herein. Users must make their own determination as to the suitability of the product for their purpose prior to use. In accordance with good practices of personal cleanliness and hygiene, handle with due care and avoid unnecessary contact with this product.