For Printing Inks and related Materials

Date of preparation:	1/23/2009
Updated:	2/2/2012
MSDS #:	147

I. PRODUCT IDENTIFICATION			
Manufacturer: Gans Ink and Supply Co, Inc.	HMIS HAZARD IDENTIFICATION		
Address: 1441 Boyd Street			
Los Angeles, CA 90033			
	Health 1		
Emergency phone: (323) 264-2200	Flammability 1		
	Reactivity 0		
	Personal B		
	Protection		
Product Class: Aqueous Coating	Manufacturer's code: S-9600		
Trade Name: Gloss Aqueous Coating			

II. COMPOSITION / INGREDIENTS

Material	CAS #	%	Exposure Limits	Units
Proprietary Mixture	NJTSRN-6000-1262	100 %	Not Established	
This product does not c Standard (29 CFR 1910		emicals as defined	by the OSHA Hazard Communic	ation

* The specific chemical identity (including CAS No.) and / or specific concentrations of the constituents contained in this vehicle are regarded as" Trade Secret" information.

III. HEALTH HAZARD INFORMATION

Effects of Overexposure Inhalation: Avoid inhalation. Not expected to be a hazard due to low volatility under standard conditions. Inhalation of mist or vapor may cause irritation of respiratory tract. Possible allergic reaction. May aggravate existing lung condition.

Skin Contact: Avoid skin contact. Slight to moderate irritant. May cause allergic reaction. Prolonged or repeated contact may result in contact dermatitis which is characterized by dryness, chapping, and reddening. May aggravate existing skin condition. This condition may make the skin more susceptible to other irritants, sensitizers, and disease. Pre-existing skin conditions may make the skin more susceptible and facilitate uptake by this route.

Eye Contact: Avoid eye contact. May cause slight irritation which is readily reversible with washing. May aggravate existing eye condition.

Ingestion: This product is considered to be practically non-toxic.

IV. FIRST AID PROCEDURES

Emergency & First Aid Procedures

Eyes: Immediately flush eyes with large amounts of water and continue flushing for 15 minutes until irritation subsides. If irritation persists, seek medical attention.

Skin: Remove contaminated clothing. Wash contaminated area thoroughly with soap and water. If redness or irritation occurs, seek medical attention. Launder contaminated clothing before reuse.

Inhalation: This material has a low vapor pressure and is not expected to present an inhalation exposure at ambient conditions. If mist or exposure is generated when the material is heated or handled, remove victim from exposure. If breathing has stopped or is irregular, administer artificial respiration and supply oxygen if it is available. If victim is unconscious, remove to fresh air and seek medical attention.

Ingestion: Do not induce vomiting. Seek medical attention. Do not give anything by mouth to an unconscious person.

Notes to Physician: Aspiration may lead to chemical pneumonitis which is characterized by pulmonary edema and hemorrhage, and may be fatal. Signs of lung involvement include increased respiration rate, increased heart rate, and a bluish discoloration of the skin. Coughing, choking, and gagging are often noted at the time if aspiration. Gastrointestinal discomfort may develop, followed by vomiting, with risk of aspiration.

V. FIRE AND EXPLOSION DATA

Flash Point °F: > 200 °F (PMCC)		Auto-ignition T	emperature °F: Not Applicable
Flammable Limits in Air	Lower Limit: N	ot Applicable	Upper Limit: Not Applicable

Extinguishing Media: Use dry chemical, foam, or CO₂ extinguishing media. **Special Fire Fighting Procedures:** Water may be ineffective, but can be used to cool containers exposed to heat or flame. Firefighters wear self contained breathing apparatus and protective gear.

Unusual Fire & Explosion Hazard: Dense smoke may be generated while burning; carbon dioxide, carbon monoxide, and other oxides may be generated as products of combustion.

VI. ACCIDENTAL RELEASE

Steps to be taken in event of spill or release: Provide adequate ventilation. Keep away from all sources of heat, flame and ignition. Absorb with an inert material such as vermiculite, sand, dirt etc. Scrape up with trowel or scoop and place in a suitable container. Clean up spill with a suitable detergent solution. Do not allow to enter waterways, drains or sewers.

VII. HANDLING AND STORAGE

Handling and Storage: Store in containers in a cool, well-ventilated area. Store in sealed containers away from heat, open flames and oxidizing materials. Fire extinguishers must be kept readily available, and personnel should be trained in their proper use. See NFPA and OSHA 1910.106. Flammable and Combustible Liquids.

Avoid prolonged contact with skin, contact with eyes, and breathing of mist or vapor. DO NOT TRANSFER to unmarked containers. Follow DOT regulations during transport.

Other Precautions: For industrial use only. Do not ingest. Consumption of food and beverages should be avoided in work areas where hydrocarbons are present. Always wash hands and face with soap and water before eating, drinking, and smoking.

VIII. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Ventilation Requirements: If vapor or mist is generated when the material is heated or handled, adequate ventilation in accordance with good engineering practice must be provided to maintain concentrations below the specific exposure or flammable limits.

Personal Protective Equipment

Respirator: Respiratory protection is not required under conditions of normal use. If vapor or mist is generated when the material is heated or handled, use an organic vapor respirator with a dust and mist filter. All respirators must be NIOSH certified. Do not use compressed oxygen in hydrocarbon atmospheres.

Skin: Use impervious synthetic rubber gloves and apron over parts of the body subject to exposure. Wash hands with soap and water before eating, smoking and / or using the toilet.

Eye: Eye protection is required under conditions of normal use. If material is handled such that it could be splashed into eyes, wear plastic face shield or splash-proof safety glasses or goggles.

IX. PHYSICAL AND CHEMICAL DATA

Boiling Range °F: > 210 °F	Vapor Density (Air = 1): > 1	
Relative Density ($H_2O = 1$): 1.05	Vapor Pressure (mm Hg @ 68°F): No Data	
Material Density Lbs./Gal: 8.74	Solubility in Water: Soluble	
%Volatiles by Weight: 2 - 4	Evaporation Rate: Slower than Butyl Acetate	
VOC: lbs/gal: 0.35 max. g/L: 42.0	Appearance/Odor: Milky liquid / Mild ammonia	
	odor	

X. STABILITY AND REACTIVITY INFORMATION

Stability (Thermal, Light, etc.): Stable	Conditions to avoid: Direct heating, open flame,	
	sources of ignition, dirt or chemical contamination.	
Hazardous Polymerization: Will not occur.	Materials to avoid: Strong oxidizers.	
Hazardous Decomposition Products: CO ₂ , CO, and other oxides may be generated as products of		
combustion.		

XI. TOXILOGICAL INFORMATION

CARCINOGEN: This product has not been identified as a carcinogen by OSHA or the National Toxicology program (NTP), or the International Agency for Research Cancer (IARC).

Mutagen:	No Data
Teratogen:	No Data
Reproductive Toxicity:	No Data

XII. ECOLOGICAL INFORMATION

This product has not been evaluated at this time As with all chemicals and products, Do Not allow to enter drains, sewers or waterways.

XIII. DISPOSAL INFORMATION

Waste Disposal Method: If recycling as ink is not possible, material may be incinerated or land filled at a licensed facility in accordance with local, state, and federal regulations.

XIV. TRANSPORT INFORMATION

Flammability Classification:	
OSHA:	Class III B
DOT Shipping Name (ground):	Non Regulated
DOT Label:	Not Applicable
DOT Identification Number:	Not Applicable

XV. REGULATORY INFORMATION

SARA Title III Section 313- Toxic Chemicals:

This material DOES NOT contain a toxic chemical in excess of 1% of the mixture (0.1% if listed toxic chemical is a carcinogen)

Clean Air Act - Hazardous Air Pollutants (HAP):

This product does not contain any HAP, as defined by the U.S. Clean Air Act Section 112 (40 CFR 61)

Clean Air Act - Ozone Depleting Substances (ODS):

This product neither contains, nor was manufactured with, a Class I or Class II ODS, as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpart A, Appendix A and B).

Section 302 – (Extremely Hazardous Substances) this product DOES NOT contain an extremely hazardous substance.

Section 311 / 312 – Pursuant to Section 311/ 312 of SARA Title III, the physical and health hazard categories for this product are identified below:

Fire Hazard:	NO
Sudden Release of Pressure Hazard:	NO
Reactivity Hazard:	NO
Immediate (Acute) Health Hazard:	NO
Delayed (Chronic) Health Hazard:	NO

TSCA Section 8(b) Inventory Status:

All component(s) of this product are listed on the TSCA Inventory.

Canada (DSL):

All component(s) of this product are listed on the Inventory.

Coalition of Northeast Governors (CONEG) Legislation:

This product meets the Coalition of Northeast Governors (CONEG) Source Reduction Council limits for the sum of the levels of Lead, Cadmium, Mercury and Hexavalent Chromium of less than 100 parts per million by weight.

U.S. State Regulations

California Proposition 65:

This product does not intentionally contain any chemicals known by the state of California to cause cancer and/or reproductive harm. Moreover, Gans Ink and Supply Co., Inc. does not routinely analyze its products for impurities which may be such chemicals.

XVI. OTHER INFORMATION

The information herein is presented in good faith, based on the data available to us and is believed to be correct as of the date hereof. However, Gans Ink and Supply Co., Inc. makes no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Gans Ink and Supply Co., Inc. assume no responsibility for any damages of any nature directly or indirectly resulting from the use of or reliance upon the information contained herein.

Users must make their own determination as to the suitability of the product for their purpose prior to use. In accordance with good practices of personal cleanliness and hygiene, handle with due care and avoid unnecessary contact with this product.



Safety Glasses Gloves

