

**Material Safety Data Sheet # 203.3 C**  
**For Printing Inks and related Materials**  
**OSHA Hazard Communication Standard, 29 CFR 1910.1200**

Date of preparation: 4/19/2013  
MSDS #: 203.3 C



**I. PRODUCT IDENTIFICATION**

Manufacturer: Gans Ink and Supply Co, Inc. Address: 1441 Boyd Street Los Angeles, CA 90033  Emergency phone: (323) 264-2200	<b>HMIS HAZARD IDENTIFICATION</b>								
	<table border="1"> <tr><td>Health</td><td>2</td></tr> <tr><td>Flammability</td><td>1</td></tr> <tr><td>Reactivity</td><td>2</td></tr> <tr><td>Personal Protection</td><td>C</td></tr> </table>	Health	2	Flammability	1	Reactivity	2	Personal Protection	C
Health	2								
Flammability	1								
Reactivity	2								
Personal Protection	C								
<b>Product Class:</b> Lithographic UV Printing Ink	<b>Manufacturer's code:</b> UV14871- 74								
<b>Trade Name:</b> New Rapicure 4 Color Process Inks									

**II. HAZARDOUS INGREDIENTS**

Material	CAS #	%	Exposure Limits	Units
Proprietary	NJTSRN 6000-1620	20.0	OSHA PEL ACGIH TLV/ TWA	Not Established Not Established
Proprietary Oligomer, Acrylic Ester #1		9.5		Not Established
Proprietary Acrylic Ester #2		9.5		Not Established
Glycerol, propoxylated, esters w/ acrylic acid	52408-84-1	15.0		Not Established Xi; R 36, H317, H319
Pentaerythritol, ethoxylated, esters w/ acrylic acid	51728-26-8	3.0		Not Established Xi, H319
Alcohol	68526-86-3	1.0		Not Established
Polyol acrylate	proprietary	< 0.5		Not Established Xi, R36
Hydroxypropyl acrylate	25584-83-2	< 1.0		Not Established Xi, R23/24/25 R34/R43
mequinol	150-76-5	< 0.2		Not Established Xn R22, Xi,R36-43
2-methyl-1-(4-methylthiophenyl)-2-morpholinopropane-1-one	71868-10-5	5.0		Not Established H360FD, H411
2-isopropyl-9H-thioxanthen-9-one	5495-84-1	2.0		Not Established

	
Health Hazard	Dangerous for the environment

Refer to section 16 for explanation of risk phrases.

### III. HEALTH HAZARD INFORMATION

Effects of Overexposure
<b>Inhalation:</b> Inhalation of mist or vapor may cause irritation or respiratory tract. Acute overexposure may result in irritation of the throat and lungs.
<b>Skin Contact:</b> Avoid skin contact. Contains materials that may cause moderate skin injury (reddening and swelling) and/or sensitization. Those known to be sensitized to Acrylate should avoid all exposure to this product.
<b>Eye Contact:</b> Avoid eye contact. Moderate irritant. Can cause burning sensation, tearing, swelling, and redness.
<b>Ingestion:</b> Do not ingest. May irritate the mouth, throat, and gastrointestinal tract.

### IV. FIRST AID PROCEDURES

Emergency & First Aid Procedures
<b>Eyes:</b> Immediately flush eyes with large amounts of water and continue flushing for 15 minutes until irritation subsides. Seek medical attention.
<b>Skin:</b> Remove contaminated clothing. Wash contaminated area thoroughly with soap and water. If redness or irritation occurs, seek medical attention. Launder contaminated clothing before reuse.
<b>Inhalation:</b> If mist or exposure is generated when the material is heated or handle, remove victim from exposure. If breathing has stopped or is irregular, administer artificial respiration and supply oxygen if it is available. If victim is unconscious, remove to fresh air and seek medical attention.
<b>Ingestion:</b> Do not induce vomiting. Seek <u>immediate</u> medical attention. Never give anything by mouth to an unconscious person.
<b>Notes to Physician:</b> Aspiration may lead to chemical pneumonitis which is characterized by pulmonary edema and hemorrhage, and may be fatal. Signs of lung involvement include increased respiration rate, increased heart rate, and a bluish discoloration of the skin. Coughing, choking, and gagging are often noted at the time of aspiration. Gastrointestinal discomfort may develop, followed by vomiting, with risk of aspiration.

### V. FIRE AND EXPLOSION DATA

<b>Flash Point °F:</b> > 212 °F	<b>Auto-ignition Temperature °F:</b> 500 °F	
<b>Flammable Limits in Air</b>	<b>Lower Limit:</b> No Data	<b>Upper Limit:</b> No Data
<b>Extinguishing Media:</b> Use water fog, foam, CO <sub>2</sub> , or dry chemical extinguishing media.		
<b>Special Fire Fighting Procedures:</b> Remove all ignition sources. Wear self-contained breathing apparatus and complete personal protective equipment when entering confined areas. Closed containers may explode when exposed to extreme heat. Closed containers may be cooled with a fine water spray. Does Not use a solid water stream as it scatter and spread the fire.		
<b>Unusual Fire &amp; Explosion Hazard:</b> High temperatures and fire conditions may cause rapid and uncontrollable polymerization which can result in explosions and the violent rupture of storage vessels. Avoid the use of a stream of water to control fires since frothing can occur. Dense smoke may be generated while burning; carbon dioxide, carbon monoxide, and nitrogen oxides may be generated as products of combustion.		

### VI. ACCIDENTAL RELEASE

<b>Steps to be taken in event of spill or release:</b> Wear protective gloves and apron. Remove all ignition sources, as spilled material may polymerize. Move leaking containers to ventilated area. Stop discharge, if it can be performed safely, and contain material. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust, vermiculite). Place in a suitable container for disposal. DO NOT allow to enter waterways, drains, sewers or lakes. Dispose of in accordance with state, local and Federal regulations. Contains chemicals that are hazardous to the environment and aquatic organisms.
--

### VII. HANDLING AND STORAGE

<b>Handling and Storage:</b> Store in containers in a dry, cool and well-ventilated area. Avoid exposure to
---

ultraviolet light and/or sunlight. Avoid temperatures higher than (60 °C) 140 °F. Keep away from all ignition sources, open flame etc. Avoid incompatible materials, such as alkalis, strong acids and chlorinated hydrocarbons. Avoid contact with skin, eyes, and breathing of mist or vapor. Wear protective chemical resistant gloves when handling. Consumption of food and beverages should be avoided in work areas. Always wash hands and face with soap and water before eating, drinking, and smoking.

**Other Precautions:** For industrial use only. Do not ingest. Always wash hands and face with soap and water before eating, drinking, and smoking.

### VIII. EXPOSURE CONTROLS AND PERSONAL PROTECTION

**Ventilation Requirements:** If vapor or mist is generated when the material is heated or handled, adequate ventilation in accordance with good engineering practice must be provided to maintain concentrations below the specific exposure or flammable limits.

#### Personal Protective Equipment

**Respirator:** Respiratory protection is not required under conditions of normal use. If vapor or mist is generated when the material is heated or handled, use an organic vapor respirator with a dust and mist filter. All respirators must be NIOSH certified. Do not use compressed oxygen in hydrocarbon atmospheres.

**Skin:** Wear protective chemical resistant gloves and apron. Safety showers are recommended.

**Eye:** Eye protection is recommended. Wear plastic face shield or splash-proof safety glasses or goggles. Eye wash stations are recommended.

### IX. PHYSICAL AND CHEMICAL DATA

<b>Boiling Range °F:</b> 212 – 518 °F	<b>Vapor Density (Air = 1):</b> > 1
<b>Relative Density (H<sub>2</sub>O = 1):</b> 1.24 – 1.31	<b>Vapor Pressure (mm Hg @ 68°F):</b> No Data
<b>Material Density Lbs./Gal:</b> 10.33 – 10.90	<b>Solubility in Water:</b> Insoluble
<b>% Volatiles by Weight:</b> < 1.4	<b>Evaporation Rate:</b> No Data <b>pH:</b> No Data
<b>VOC: lbs/gal:</b> < 0.153 <b>g/L:</b> 18.3	<b>Appearance/Odor:</b> Colored Liquid

### X. STABILITY AND REACTIVITY INFORMATION

<b>Stability (Thermal, Light, etc.):</b> Stable under normal conditions of storage and use.	<b>Conditions to avoid:</b> Avoid exposure to ultraviolet light, and/or sunlight. Avoid excessive heat, <b>Do not</b> store above (60°C) 140° F. Hazardous exothermic polymerization can occur when heated. Hazardous polymerization can occur if exposed to direct sunlight.
<b>Hazardous Polymerization:</b> High temperatures (>140°F) and oxygen deficient atmosphere reduce inhibitors effectiveness and may cause polymerization, raising the temperature and pressure, possible rupturing the container. <b>Do NOT</b> blanket or mix with nitrogen or other inert gases as this renders the inhibitor ineffective.	<b>Materials to avoid:</b> Initiators including peroxides, strong oxidizing agents, copper, copper alloys, carbon steel, iron, rust, nickel, cobalt and strong bases.
<b>Hazardous Decomposition Products:</b> Carbon monoxide, Carbon dioxide and other oxides may be generated as products of combustion.	

### XI. TOXICOLOGICAL INFORMATION

**CARCINOGEN:** This product has not been identified as a carcinogen by OSHA or the National Toxicology Program (NTP), or the International Agency for Research Cancer (IARC).

**Mutagen:** No Data

**Teratogen:** No Data

**Reproductive Toxicity:** No Data

#### Components:

Glycerol propoxylated,  
Esters w/ acrylic acid

52408-84-1

[NLP 500-114-5]

Oral LD50 > 5000 mg/kg irritating to eyes  
Dermal OCED 404, 0-8 = 0.6 (Rabbit) not classified

methyl-1(4-methylthiophenyl)-  
2-morpholinopropan-1-one 71868-10-5  
Oral LD50 Rat: 1800 mg/kg literature

Polyseter Acrylate  
Oral LD50 Rat: > 2,000 mg/kg  
Dermal LD50 Rabbit: >> 2,000 mg/kg

## XII. ECOLOGICAL INFORMATION

This product has not been evaluated at this time. Contains chemicals that are toxic to aquatic organisms. **Do Not** allow to enter sewers, drains or waterways. Hazardous for water. Hazardous for fish and plankton in water bodies.

Aquatic Toxicity:  
71868-10-5 2-methyl-1-(4-methylthiophenyl)-2-morpholinopropan-1-one  
EC50/72h 1.7 mg/l algae OECD 121 ads.coeff. 5.3= log Koc (-)

## XIII. DISPOSAL INFORMATION

**Waste Disposal Method:** If discarded in its original unused form, this product Does **NOT** exhibit the characteristics of a RCRA hazardous waste as defined under 40CFR261. Waste materials should be dumped or buried in an approved landfill, or incinerated in a suitable combustion chamber. Disposal must comply with all local, state, and federal regulations. Of the methods of disposal currently available, it is recommended that an alternative be selected according to the following order of preference, based upon environmental acceptability:

- 1) Recycle or rework if at all feasible.
- 2) Incinerate at an authorized facility.
- 3) Treat at an acceptable waste treatment facility.

## XIV. TRANSPORT INFORMATION

### Flammability Classification:

<b>OSHA:</b>	Class III B
<b>US DOT (Ground):</b>	Not Regulated
<b>IMO/ IMDG (Sea):</b>	Not Regulated
<b>IATA/ ICAO (Air):</b>	Not Regulated
<b>Canadian TDG:</b>	Not Regulated

Not classified as dangerous in the meaning of transport regulations.

## XV. REGULATORY INFORMATION

### U.S. Federal Regulations

#### **SARA Superfund Amendments and Reauthorization Act of 1986 Title III Section 313:**

This material does Not contain chemicals subject to the reporting requirements of the SARA Superfund Amendments and Reauthorization Act.

**Section 302** – Extremely hazardous substances: This product does not contain any components regulated under Section 302 (40 CFR 355) as EHS.

**Section 311/312** – Hazard Categories: Pursuant to Section 311/312 of SARA Title III, the physical and health hazard categories for this product are identified below:

Fire Hazard – NO  
Sudden Release of Pressure Hazard – NO  
Reactivity Hazard – YES  
Immediate (acute) Health Hazard – YES  
Delayed (chronic) Health Hazard – YES.

**HAP Clean Air Act - Hazardous Air Pollutants**

This product does not contain any HAP, as defined by the U.S. Clean Air Act Section 112 (40 CFR 61)

**DSL (Canadian Domestic Substances List):**

All components of this product are either exempt or listed on the DSL.

**TSCA Section 8(b) Inventory Status:**

All component(s) of this product are either exempt or listed on the TSCA Inventory.

**OSHA (Occupational Safety & Health Administration) Hazard Communication Standard, 29 CFR 1910.1200**

This product is considered to be a hazardous substance under OSHA regulations.

**U.S. State Regulations**

**California Proposition 65:**

This product contains a chemical(s) known by the state of California to cause reproductive harm.

<u>Chemical</u>	<u>CAS#</u>	<u>%</u>
Toluene	108-88-3	Trace amounts

**XVI. OTHER INFORMATION**

**Risk Phrases:**

Xn: Harmful Chemical that may cause damage to health  
Xi: Irritant, Chemicals that may cause inflammation to the skin or other mucous membranes.  
R22: Harmful if swallowed  
R23/24/25: Toxic by inhalation, in contact with skin and if swallowed.  
R34: Causes burns  
R36: Irritating to eyes  
R36- 38: Irritating to eyes, skin and respiratory  
R43: May cause sensitization by skin contact

H317: May cause an allergic reaction  
H319: Causes serious eye irritation  
H360FD: May damage fertility. May damage the unborn child.  
H411: Toxic to aquatic life with long lasting effects.

The information herein is presented in good faith, based on the data available to us and is believed to be correct as of the date hereof. However, Gans Ink and Supply Co., Inc. makes no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Gans Ink and Supply Co., Inc. assumes no responsibility for any damages of any nature directly or indirectly resulting

from the use of or reliance upon the information contained herein. Users must make their own determination as to the suitability of the product for their purpose prior to use. In accordance with good practices of personal cleanliness and hygiene, handle with due care and avoid unnecessary contact with this product.

C

Safety Glasses  
Gloves  
Apron

