Material Safety Data Sheet # 234.1

For Printing Inks and related Materials OSHA Hazard Communication Standard, 29 CFR 1910.1200
 Date of preparation:
 5/14/93

 Updated:
 6/29/2010

 Supersedes:
 5/5/2010

I. PRODUCT IDENTIFICATION					
Manufacturer: Gans Ink and Supply Co, Inc.		HMIS HAZARD IDENTIFICATION			
Address:	1441 Boyd Street				
	Los Angeles, CA 90033				
			Health	1	
Emergency phone: (323) 264-2200			Flammability	1	
			Reactivity	1	
			Personal	В	
			Protection		
Product Cla	ss: Lithographic Printing Ink	Manufacturer's code: X101302, X100330,			
		X101066, X102657, X102843, X101966, X103155,			
		X103318, etc.			
Trade Name: Coin Reactive with Fluorescent					

II. HAZARDOUS / INGREDIENTS

Material	CAS #	%	Exposure Limits	Units
This product is conside CFR 1910.1200.	ered Non-Hazardous by	y definition of O	SHA Hazard Communication St	tandard 29

III. HEALTH HAZARD INFORMATION

Effects of Overexposure

Inhalation: Avoid inhalation. Primary route of entry. This product has a low vapor pressure and is not expected to present an inhalation hazard at ambient conditions. Caution should be taken to prevent aerosolization or misting of this product. The threshold limit value (TLV) for this product as oil mist is 5 mg/M³. Exposures below 5 mg/M³ appear to be without significant health risk. Excessive inhalation may cause headaches, dizziness and nausea or irritation of nasal and respiratory tract. Acute overexposure may result in irritation of the throat and lungs. Chronic exposure to high concentrations of aerosols or mists to laboratory animals has resulted in non-specific symptoms related to the nervous system, gastrointestinal tract, and lungs.

Skin Contact: Avoid skin contact. Primary route of entry. This product is non-irritating to the skin upon direct contact. Prolonged or repeated contact may result in contact dermatitis which is characterized by dryness, chapping, and reddening. This condition may make the skin more susceptible to other irritants, sensitizers, and disease. Pre-existing skin conditions may make the skin more susceptible and facilitate uptake by this route.

Eye Contact: Avoid eye contact. This product may be slightly irritating to the eyes upon direct contact. This product has a low vapor pressure and is not expected to present a hazard to the eyes at ambient conditions. Exposure to high concentrations of vapors may be irritating to the eyes.

Ingestion: Do not ingest. Ingestion of small quantities is usually nonfatal unless aspiration occurs. Severe oral intoxication will lead to intense burning of the throat and may result in drowsiness, dullness, numbness, and headache followed by dizziness, weakness, and nausea. Loss of consciousness and convulsions followed by death may result. See *Notes to Physician* section below.

IV. FIRST AID PROCEDURES

Emergency & First Aid Procedures

Eyes: Immediately flush eyes with large amounts of water and continue flushing for 15 minutes until irritation subsides. If irritation persists, seek medical attention.

Skin: Remove contaminated clothing. Wash contaminated area thoroughly with soap and water. If redness or irritation occurs, seek medical attention.

Inhalation: This material has a low vapor pressure and is not expected to present an inhalation exposure at ambient conditions. If mist or exposure is generated when the material is heated or handled, remove victim from exposure. If breathing has stopped or is irregular, administer artificial respiration and supply oxygen if it is available. If victim is unconscious, remove to fresh air and seek medical attention.

Ingestion: Do not induce vomiting. Seek immediate medical attention.

Notes to Physician: Aspiration may lead to chemical pneumonitis which is characterized by pulmonary edema and hemorrhage, and may be fatal. Signs of lung involvement include increased respiration rate, increased heart rate, and a bluish discoloration of the skin. Coughing, choking, and gagging are often noted at the time if aspiration. Gastrointestinal discomfort may develop, followed by vomiting, with risk of aspiration.

V. FIRE AND EXPLOSION DATA

Flash Point °F: >260 F	Auto-ignition	Auto-ignition Temperature °F: 428 ASTM E-659	
Flammable Limits in Air	Lower Limit: No Data	Upper Limit: No Data	
Extinguishing Media: Use, foam, CO ₂ , or dry chemical extinguishing media.			
Special Fire Fighting Procedures: Water may be ineffective, but can be used to cool containers exposed to			
heat or flame. During a fire, irritating and toxic gases may be formed. Do not breathe smoke or fumes.			
Isolate the area. Firemen wear suitable protective clothing, and breathing apparatus.			
Unusual Fire & Explosion Hazard: Dense smoke may be generated while burning; carbon dioxide, carbon			
monoxide, and other oxides may be generated as products of combustion.			

VI. ACCIDENTAL RELEASE

Steps to be taken in event of spill or release: Absorb with inert material such as vermiculite, clay or dirt. Scrape up with trowel or scoop and place in a suitable container. Clean up with a suitable solvent.

VII. HANDLING AND STORAGE

Handling and Storage: Store in containers in a cool, well-ventilated area. Keep containers closed when not in use. Keep away from excessive heat, open flame or sources of ignition. Avoid prolonged contact with skin, eyes, and breathing of mist or vapor. Always wash hands and face with soap and water before eating, drinking, and smoking.

Other Precautions: For industrial use only. Do not ingest. Consumption of food and beverages should be avoided in work areas where hydrocarbons are present.

VIII. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Ventilation Requirements: If vapor or mist is generated when the material is heated or handled, adequate ventilation in accordance with good engineering practice must be provided to maintain concentrations below the specific exposure or flammable limits.

Personal Protective Equipment

Respirator: Respiratory protection is not required under conditions of normal use. If vapor or mist is generated when the material is heated or handled, use an organic vapor respirator with a dust and mist filter. All respirators must be NIOSH certified. Do not use compressed oxygen in hydrocarbon atmospheres. **Skin:** No skin protection is required for single, short duration exposures. For prolonged exposures, use impervious synthetic rubber clothing (boots, gloves, etc.) over parts of the body subject to exposure **Eye:** If material is handled such that it could be splashed into eyes, wear plastic face or splash-proof safety goggles.

IX. PHYSICAL AND CHEMICAL DATA

Boiling Range ° F: 300 - 610	Vapor Density (Air = 1): >1
Relative Density (H₂O = 1): 1.53 – 2.94	Vapor Pressure (mm Hg @ 70°F): 0.1
Material Density Lbs./Gal: 12.74 – 24.48	Solubility in Water: Insoluble

%Volatiles by Weight: 10.1 max.	% Solids by Weight: 89.9
VOC: lbs/gal: 2.47 g/L: 297	Appearance/Odor: Cream colored paste

X. STABILITY AND REACTIVITY INFORMATION

Stability (Thermal, Light, etc.): Stable	Conditions to avoid: Excessive heat, open flame	
	and sources of ignition.	
Hazardous Polymerization: Will not occur.	Materials to avoid: Strong Oxidizers	
Hazardous Decomposition Products: CO ₂ , CO, and other oxides may be generated as products of		
combustion.		

XI. TOXICOLOGICAL INFORMATION

CARCINOGEN: This product has not been identified as a carcinogen by OSHA or the National			
Toxicology Program (NTP), or the International Agency for Research Cancer (IARC).			
Mutagen:	No Data		
Teratogen:	No Data		
Reproductive Toxicity:	No Data		

XII. ECOLOGICAL INFORMATION

This product has not been evaluated at this time. As with all products Do Not allow product to enter sewers, drains or waterways.

XIII. DISPOSAL INFORMATION

Waste Disposal Method: If recycling as ink is not possible, material may be incinerated or land filled at a licensed facility in accordance with local, state, and federal regulations.

XIV. TRANSPORT INFORMATION

Flammability Classification:	Combustible
OSHA:	Class III B
DOT (Ground):	Not Regulated
IATA / ICAO (Air):	Not Regulated
IMO / IMDG (Sea)	Not Regulated
TDG (Canada):	Not Regulated

XV. REGULATORY INFORMATION

SARA Title III Section 313:

This material Does Not contain chemicals subject to the reporting requirements of the SARA Superfund Amendments and Reauthorization Act.

TSCA Section 8(b) Inventory Status:

All component(s) of this product are either exempt or listed on the TSCA Inventory.

U.S. State Regulations

FDA: This product is not registered with the FDA.

Coalition of Northeast Governors (CONEG) Legislation:

This product is in compliance with CONEG (i.e. total cadmium, hexavalent chromium, lead and mercury < 100 ppm)

California Proposition 65:

This product contains a chemical known to the state of California to cause cancer

Chemical	<u>CAS #</u>	<u>%</u>	
Benzene	71-43-2	Trace amount	Cancer, Birth Defect
Formaldehyde	00050-00-0	Trace amount	Cancer

This product contains less than 0.1 % free formaldehyde and may be capable of outgassing formaldehyde at levels in excess of OSHA's Action Level under some conditions of use. Formaldehyde is a potential cancer hazard. Long term may result in dermatitis or respiratory sensitization for sensitive individuals.

OSHA Hazard Communication Standard , 29 CFR 1910.1200

This product is not considered hazardous as defined.

XVI. OTHER INFORMATION

The information herein is presented in good faith, based on the data available to us and is believed to be correct as of the date hereof. However, Gans Ink and Supply Co., Inc. make no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Gans Ink and Supply Co., Inc. assume no responsibility for any damages of any nature directly or indirectly resulting from the use of or reliance upon the information contained herein. Users must make their own determination as to the suitability of the product for their purpose prior to use.